

PFT G 4 smart

Perfect work for a low investment


Specially developed for small budget, but still with convincing quality. PFT G 4 smart does perfect work for little money. The machine offers an efficient and reliable solution for every challenge in tough daily use.



TECHNICAL DATA

Part no.	00 25 73 59
Working pressure	max. 30 bar
Conveying output	max. 35 l/min
Conveying distance	up to 30 m
Motor	400 V, 3 Ph, 50 Hz, 5.5 kW, 400 rpm
Rotor / Stator	D 6-3
Spraying gun	smartline DN25 F14 200 Geka
Air compressor	COMP M-250, 400 V, 3 Ph, 50 Hz, 0.9 kW, 250 l/min
Material outflow	DN25 male part
Material hose	RONDO DN25 - 10 m
Air hose	DN12 Ewo male part Geka - 11 m
Water pump	AVP 500 400 V, 3 Ph, 50 Hz, 0.37 kW
Operation and control	Start/Stop incl. water pump control
Hopper content	145 l
Dimensions: L/W/H	1,200 / 720 / 1,530 mm
Filling height	910 mm
Weight	~285 kg

Kindly note:
Conveying distance depends on the used materials.
Images similar



ADVANTAGES AT A GLANCE



- 1 Large fine mesh water filter
 - 2 Reinforced tubular frame and robust wheel mounts
 - 3 Forklift straps and crane lifting eyes
 - 4 Easy, fast and efficient – the filling of the machine with material:
 - Direct filling from silo by using the delivery hood
 - Filling with bagged cargo
 - Pneumatic filling from silo by using conveying equipment PFT SILOMAT and injection hood
 - 5 PFT DUSTCATCHER to reduce dust formation
- Switches and connectors are within the basic frame
 - Flexible mixing intensity thanks to two water inlets
 - Safe transport thanks to four holders with folding mechanism
 - Maintenance-friendly – water manifold and pressure switch are easily accessible

Images similar

FIELDS OF APPLICATION

- Gypsum plaster
- Lime-gypsum plaster
- Cement plaster
- Insulation material
- Lime-cement plaster
- Fango material
- Insulation plaster
- Recessed material
- Masonry mortar
- Floor screed
- Levelling compound
- Adhesive mortar

ACCESSORIES

- Extension cable 5 x 4 mm², RED 5-32 A - 50 m
- DUSTCATCHER G 4 complete
- Injection hood
- Delivery hood
- ZARGOMAT pro DN25-360°
- JETSET pro DN25 Ewo
- G 4 smart without pressure booster pump

PART NO.

- 20 42 39 00
- 00 53 97 16
- 20 60 02 13
- 20 60 05 00
- 00 42 00 58
- 00 41 89 75
- 00 26 06 22

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net/360_G4
www.youtube.com/knaufpften

Download now! APP: PFT – Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · DE-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT G 4 smart – EN/02.21/PFT