

# PFT SWING L FC-230V airless c

The high-pressure pump with RotaAirless technology digital control system

The powerful PFT SWING airless has a high machine utilization due to the many different application such as spraying, filling, gluing and reinforcing, the powerful PFT SWING airless has a high machine utilization rate. The new color display of the control system (c) provides all relevant machine information at a glance and enables intuitive operation.



## TECHNICAL DATA


Part no.	00803680
Part no.	00803683 (with bag squeezer)
Conveying capacity	up to 6.5 l / min , continuously adjustable
Conveying distance	up to 20 m
Working pressure	max. 140 bar
Rotor/Stator	306 airless
Motor	230 V, 1 Ph, 50 Hz, 3 kW, 0 – 280 rpm
Material outflow	DN12 female   1/2" external thread
Material hose	RONDO airless DN12 – 20 m
Spraying gun	In Line Texspray
Spraying cap	RAC X 545
Connection cable	BLA 2-16 A – 5 m
Filling height	720 mm
Hopper content	70 l
Dimensions: L / W / H	1,430 / 500 / 972 mm
Total weight	~ 105 kg

ROTA AIRLESS

More quiet!

More robust!

More economical!



## ADVANTAGES AT A GLANCE



- 1** Material hopper one-piece, no back taper  
Reduced material adhesion – quick and easy cleaning
- 2** Protective grid, low-lying
- 3** 3 Quick pump replacement on construction site
- 4** Intuitive operation using digital PFT Control system (c)  
- Access password as theft protection  
- With plain-text error messages
- 5** Tube bracket, integrated
- 6** Material filter
- 6** Constant electronic monitoring through pressure sensor
- 7** Puncture proof wheels
- 6** Pump, valveless – RotaAirless technology:  
Improved spray quality due to an additional kneading effect in the pump
- 6** Pressure control via digital display
- 6** Idling protection – extends the lifetime of the pump
- 6** Conveying distance up to 20 metre – flexible hose with kink protection on machine outlet
- 6** Various fields of application: spray plaster, grainy material up to 3 mm, colour\*
- 6** Low noise, compact and powerful
- 6** Easy handling on construction site
- 6** Robustly designed and suitable for construction site

\* Please consider approval of colours.  
Do not use with solvent-containing colours

### FIELDS OF APPLICATION

- Spray plaster
- Grainy material up to 3 mm\*
- Colour\*\*

\*\* Not with Stator 306 airless  
\*\* Please consider approval of colours. Do not use with solvent-containing colours.



### ACCESSORIES

- Bag squeezer
- Conversion kit – for air-assisted spraying of spray plaster
- Conversion kit – grainy material
- Conversion kit – colour
- CEE current manifold 400 V  
RED 5-16 A | 3x BLA 2-16 A

### PART NO.

00459811  
00504344  
00518542  
00503759  
00495147



### The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT-brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

[www.pft.net/360](http://www.pft.net/360)  
[www.youtube.com/knaufpft](http://www.youtube.com/knaufpft)

### Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net [www.pft.net](http://www.pft.net)

All rights and technical modifications reserved. The respective current version applies. Our warranty refers only to the perfect condition of our machines. Figures given in relation to consumption, quantity and design as well as performance data are based on experience and cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always valid. Illustrations may show customized versions, which are not included in the standard scope of delivery. Change, reprint and photomechanical as well as electronic reproduction, also of excerpts, is only permitted with the explicit approval of Knauf PFT GmbH & Co. KG.

PFT SWING airless FC-230V – EN/03.24/PFT