

DV18DE(H4Z)
18V Impact Driver Drill

Barcode 4966376404773

Maximum torque of 70Nm

RFC (Reactive Force Control)

13mm Metal keyless chuck



Specifications

Voltage	18V
Motor type	Brushless
Switch type	Trigger
Drill chuck type	Keyless metal chuck
Chuck capacity	1.5 - 13mm
Light	LED White
Clutch stages	22 (Torque 1.0 - 4.5Nm)
Maximum Torque Hard Joint	70Nm
Maximum Torque Soft Joint	40Nm
No load speed - low	0 - 550 rpm
No load speed - high	0 - 2,000rpm
No load impact rate	30,000 ipm
Capacity	Bricks: 13mm
	Masonry: 21mm
	Wood: 52mm
	Steel & Aluminium: 13mm
	Small screw: M6
	Wood screw: M10 x 100mm
RFC (Reactive Force Control)	Yes
Forward / Reverse Mode	Yes
Spindle Lock	Yes
Dimensions (L x H x W)	159 x 238 x 78mm
Weight (including the battery)	1.9kg
Battery	Compatible with HIKOKI Multi Volt & 18V Slide batteries
Included accessories	Hook & driver bit

Features

Maximum torque of 70Nm

Equipped with the RFC function that is safety feature to reduce the tool from jerking

Heavy duty 13mm single sleeve metal keyless chuck with automatic spindle lock

Compatible with the HIKOKI MultiVolt battery

Selling Points

Maximum torque of 70Nm

RFC (Reactive Force Control)

13mm Metal keyless chuck

Applications

Tightening and loosening wooden screws, machine screws and self tapping screws

Drilling into wooden materials, plastics, mild steel and aluminium

Drilling into bricks and concrete blocks.