

WH18DC(H4Z) 18V Brushless Impact Driver

Barcode 4966376402922

Compact and easy to use

Highly visible 3-LED lights

Triple hammer

5 step tightening mode selector

Conforming to IP56

Compatible with the HiKOKI MultiVolt and 18V slide batteries



**BRUSH
LESS**
Brushless Motor

**TRIPLE
HAMMER**

IP56

Specifications

Voltage	18V
Motor type	Brushless
Switch type	Variable speed trigger switch
Capacity	Small screw 4 - 10 mm
	Ordinary screw 5 - 18 mm
	High-tension bolt 5 - 14 mm
	Self drilling screw 3.5 - 6 mm
Maximum Tightening torque	210Nm
No-load rotation speed	Soft: 0 - 900rpm
	Power: 0 - 3,400rpm
	Bolt: 0 - 2,900rpm
	Bolt single: 0 - 2,900rpm
	Self-drilling screw: 0 - 3,700rpm
Impact rate	Soft: 0 - 1,900ipm
	Power: 0 - 4,000ipm
	Bolt: 0 - 4,000ipm
	Bolt single: 0 - 4,000ipm
	Self drilling screw: 0 - 2,100ipm
No-load sound pressure level	74.8dB
Weight (including battery BSL36A18)	1.6kg
Dimensions (L x H)	114 x 241mm
Battery	Compatible with HiKOKI Multi Volt & 18V slide batteries
Included accessories	Hook

Features

Compact and easy to use with a 114mm long in head length

Highly visible 3-LED lights to improve visibility of the work in a dark workplace

Triple hammer anvil reduces vibration and "cam-out"

5 tightening modes: Soft mode for small screws, Power mode for wood screws, Bolt mode for bolts, Bolt mode (single) for small bolts & Self drilling mode for self drilling screws

Conforming to IP56 (dust and water resistant)

Compatible with the HiKOKI MultiVolt and 18V slide batteries

Selling Points

Compact and easy to use body at 114mm long

Highly visible 3-LED lights

Triple hammer anvil reduces vibration and "cam-out"

5 step tightening mode selector

Conforming to IP56 (dust and water resistant)

Compatible with the HiKOKI MultiVolt and 18V slide batteries

Applications

Driving and removing of machine screws, wood screws & tapping screws