

## BSL3640MVT

### HiKOKI T-PWR MULTI VOLT Battery

36V/18V - 4.0/8.0 Ah

- TABLESS CELL TECHNOLOGY
- HIGH POWER AND PERFORMANCE FOR DEMANDING JOBS



 Compatible

#### Specifications

|                                |                  |
|--------------------------------|------------------|
| Voltage                        | 36V/18V          |
| Battery capacity 36V           | 4.0 Ah           |
| Battery capacity 18V           | 8.0 Ah           |
| Battery level indicator        | ✓                |
| Battery dimensions (L x W x H) | 134 x 83 x 77 mm |
| Package dimensions (L x W x H) | 141 x 90 x 90 mm |
| Charging time with UC36YSL2    | ≈ 40 min.        |
| Weight                         | 980 g            |

#### Features

Maximum power output up to 2,160 W: Delivering up to 50% more power<sup>1</sup> to handle heavy-duty applications with ease and efficiency

Longer runtime: Run longer and stay cool even during demanding applications thanks to the tabless cell technology that generates less resistance and less heat

Quick charging: Short charging time of around 40 minutes with the UC36YSL2 charger

One battery for both 36V and 18V tools: Can power a wide range of HiKOKI 36V and 18V. power tools to complete both light and heavy-duty tasks

Increased durability: The impact-resistant design (rubber overmolded base) enhances the durability of the battery

<sup>1</sup> Compared to BSL36B18X (1,440 W Output) and BSL36B18 (1,440 W Output) batteries.

<sup>2</sup> Standard accessories vary by country or area.

