

REC RRD2



Model	PU	VP	Art. Nr.	EAN
REC RRD2	1		71112001	9002719044567

Characteristics

- New laser reception technology: precision mm display of the height difference even at large distances
- Adjustable sensor sensitivity in 4 levels
- Large 90-mm laser reception window for rapid localization of laser beam
- Extra-large LCD display on the front and back for comfortable working
- Optical and acoustic signaling for fast positioning of the receiver
- Automatic switch-off

Manufacturer


SOLA-Messwerkzeuge GmbH & Co KG
Unteres Tobel 25
6840 Götzis, Austria
T +43 5523 533800
www.sola.at, sola@sola.at

Technical details

Item description	Receiver REC RRD2 EVO 360
Dimensions	192 x 73 x 29 mm (without bracket)
Measuring tolerance	superfine: ± 1.00 mm / fine: ± 2.00 mm / medium: ± 5.00 mm / rough: ± 10.00 mm
Operating temperature	-15 °C to +60°C
Protection class	IP66
Power supply	4 x 1.5 V (AA) batteries
Operating time (at 20 °C)	48 hrs
Application range (radius)	300 m
Weight	257 g (without batteries)

Included accessory

- Clamp RRD1 + RRD2
- 4 x 1.5 V (AA) batteries



SOLA-Messwerkzeuge GmbH & Co KG
Unteres Tobel 25
6840 Götzis, Austria
T +43 5523 53380-0
sola@sola.at, www.sola.at

SOLA-Messwerkzeuge GmbH & Co. KG
Heuriedweg 69
88131 Lindau, Germany
T +49 8382 28585
sola@sola.at, www.sola.de

SOLA Suisse AG
Grenzstrasse 24
9430 St. Margrethen, Switzerland
T +41 71 740 1616
info@solasuisse.ch
www.solasuisse.ch