



# Einhell

# CLASSIC

Angle Grinder

**TC-AG 125/850 Kit**

**Item No.: 4430977**

Ident No.: 21011

Bar Code: 4006825661750

The Einhell TC-AG 125/850 Kit angle grinder is a powerful allrounder in the workshed, house and garage. Extra user safety is provided by a wheel guard. Another feature contributing to safer operation is the restart safeguard. The spindle locking system enables the tool to be changed easily and conveniently. On-the-job flexibility is catered for by a metal gear head. The additional handle can be fitted in two different positions, permitting comfortable handling in every situation. This angle grinder set comes with three cutting disks (Ø 125 mm) and a fin grinding disk. Everything has its place in a practical Einhell 45/22 bag.

## Features & Benefits

- Disk guard for extra user safety
- Spindle locking system for changing tools easily and conveniently
- Metal gear head for flexible operation
- Restart safeguard for safe working
- Additional handle can be fitted in 2 positions
- Incl. 3x cutting disc and 1x fin grinding disc
- Supplied in the practical Einhell bag 45/22

## Technical Data

- |                 |                         |
|-----------------|-------------------------|
| - Mains supply  | 220-240 V   50 Hz       |
| - Power         | 850 W                   |
| - Idle speed    | 12000 min <sup>-1</sup> |
| - Disc diameter | 125 mm                  |

## Logistic Data

- |                                      |                    |
|--------------------------------------|--------------------|
| - Product weight                     | 1.78 kg            |
| - Gross weight single packaging      | 4.55 kg            |
| - Dimensions single packaging        | 444 x 310 x 180 mm |
| - Pieces per export carton           | 2 Pieces           |
| - Gross weight export carton         | 15 kg              |
| - Dimensions export carton           | 520 x 330 x 395 mm |
| - Container quantity (20"/40"/40"HC) | 1068   2160   2470 |



FLAT & ROBUST




EASY CHANGE




FLEXIBLE-  
& POSITIONS




INCL.



Ø 125 mm



33 mm



ERGONOMIC