




**EAN:** 4013288217561  
**Part number:** 05075681001  
**Article number:** Click-Torque C 3 Set 2

**Size:** 545x132x95 mm  
**Weight:** 3366 g  
**Country of origin:** TW  
**Customs tariff number:** 82041100

- For fitting security-relevant cement screws with defined torque moments as per screw manufacturer instructions
- Click-Torque C 3 torque wrench with reversible ratchet (measuring range: 40-200 Nm; precision  $\pm 3\%$  as per DIN EN ISO 6789-1:2017-07)
- 8790 C Impaktor socket wrench inserts for the application with compressed air or electrically driven impact wrenches with 12.5 mm = 1/2" drive (13 mm to 21 mm)
- Extension 8894 SC, short, 1/2" with cross-bore and the ring socket to secure the locking ring/locking pin of machine operated tools
- 11-piece set in premium textile tool box

11-piece set for fitting security-relevant cement screws with defined torque moments as per screw manufacturer instructions. With Take it easy tool finder with colour coding and size stamping - for easy and fast location of the required tool.



**Web link**  
<https://www.wera.de/en/05075681001>

Wera - Click-Torque C 3 Set 2  
05075681001 - 4013288217561

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

**For fitting cement screws**



The tool set is particularly suitable for fitting security-relevant cement screws with defined torque moments as per screw manufacturer instructions.

**For electric or pneumatic wrenches**



The Impaktor technology ensures above-average service life of the Impaktor socket wrench plug-ins even under extreme conditions.

**Cross hole and ring socket**



Thanks to the hole and the ring socket, the tools can be held securely on the power tool with a safety pin or an O-ring.

**Click-Torque Wrench series**



Click torque wrench in unmistakable Wera design.

**Exact**



Precision of  $\pm 3\%$  as per DIN EN ISO 6789-1:2017-07.

**Easy and safe**




Easy setting and saving of the desired torque value; easy to read on main and fine scales.

**Setting with Speed**




With audible and tactile locking when the scale values are reached.

**Release mechanism**



On reaching the desired torque value, an audible and tactile mechanism is triggered.



**Web link**

<https://www.wera.de/en/05075681001>


Wera - Click-Torque C 3 Set 2  
05075681001 - 4013288217561

Wera Werkzeuge GmbH  
Korzeter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: info@wera.de

Set contents:


Click-Torque C 3 torque wrench with reversible ratchet, 40-200 Nm, 1/2" x 40-200 Nm

05075622001 1x 1/2" x 40-200 Nm



8790 C Impaktor socket with 1/2" drive, 13 x 38 mm

05004570001 1x 13 x 38 mm  
05004571001 1x 14 x 38 mm  
05004572001 1x 15 x 38 mm  
05004573001 1x 16 x 38 mm  
05004574001 1x 17 x 38 mm  
05004575001 1x 18 x 38 mm  
05004576001 1x 19 x 38 mm  
05004577001 1x 20 x 38 mm  
05004578001 1x 21 x 38 mm




8894 SC extension, short, 1/2", 1/2" x 125 mm

1x 1/2" x 125 mm



МАГАЗИН МАЙСТОРА  
БАШ ПРОФЕСИОНАЛНИ РЕШЕНИЯ



Web link

<https://www.wera.de/en/05075681001>

Wera - Click-Torque C 3 Set 2  
05075681001 - 4013288217561

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: info@wera.de