

DTM53Z

Напрежение:	18 V LXT
Капацитет на батерията:	1,5 / 2,0 / 3,0 / 4,0 / 5,0 / 6,0 / 9,0 / 12,0Ah
Вид на батерията:	Li-ion
Тип на захвата за:	OIS
Ъгъл на отклонение :	3,2°
Колебания в минута:	6.000 - 20.000min ⁻¹
Шум: звуково налягане:	80dB(A)
Шум: отклонение:	3dB(A)
Вибрации: рязане с потапяне на диска:	12,0m/s ²
Вибрации: рязане със сегментиран диск:	4,3m/s ²
Вибрации: остъргване:	4,3m/s ²
Вибрации: шлайфане:	4,3m/s ²
Вибрации: отклонение (K):	1,5m/s ²
Размери (Д x Ш x В):	312 x 80 x 120mm
Тегло:	1,7kg



- Versatile tool suitable for DIY enthusiasts and professionals to handle various tasks such as DIY projects, flooring or drywall installation, removing grout, scraping residual glue or caulk, sanding hard to reach areas ...
- BL motor with constant speed control for higher efficiency under load.
- Slim grip design (circumference 139 mm) for improved handling vs. DTM51.
- Tool-less accessory change with OIS clamp.
- Variable speed control (dial), soft start, lock-on, and anti-restart.
- Dust collection capable during sanding (with optional dust attachment).
- XPT-compatible (enhanced dust & water resistance)* for jobsite robustness. *Except when using BLB182 battery (IPX0, not XPT-compatible)
- 12 angle settings at every 30° from 0° to 360°
- Suitable for wood flooring, tile, plaster, drywall, PVC, and a variety of other applications