

**LXT** | **18V**

## SLIM-LINED PERFORMANCE

**DTM53**  
BRUSHLESS MULTI TOOL

UP TO **20,000**  
OSCILLATIONS  
PER MINUTE

**3.2°** TOTAL  
OSCILLATION  
ANGLE

**OIS** BLADE  
FITMENT  
FOR MAXIMUM COMPATIBILITY





# LXT MULTI TOOL RANGE

LXT 18V | 36V

## DTM52



## DTM53



**BLADE FITMENT**

STARLOCK

OIS

**MAX. POWER OUTPUT**

370W  
WITH BL1860

390W  
WITH BL18120

**OSCILLATION ANGLE**

3.6° (1.8° LEFT/RIGHT)

3.2° (1.6° LEFT/RIGHT)

**OSCILLATIONS PER MINUTE**

10,000 – 20,000 OPM

6,000 – 20,000 OPM

**BLADE CHANGE SYSTEM**

TOOL-LESS

TOOL-LESS

**VIBRATION LEVEL**

SANDING: 0.5M/S<sup>2</sup> | CUTTING: 1.0M/S<sup>2</sup>

SANDING: 4.3 M/S<sup>2</sup> | CUTTING: 12.0M/S<sup>2</sup>

**VARIABLE SPEED CONTROL**

6 STAGE DIAL

6 STAGE DIAL

**WEIGHT (SKIN)**

1.4KG

1.4KG

**WEIGHT (BL1860B)**

2.1KG

2.1KG

**DIMENSIONS (LxWxH)**

276MM x 95MM x 122MM

283MM x 80MM x 107MM

**MORE VERSATILITY**

TRADE DRIVEN • TRUSTED INVESTMENT

**EXPERIENCE MORE™**

## SPECIFICATIONS

<b>BLADE FITMENT</b>	OIS
<b>MAX. POWER OUTPUT</b>	390W (WITH BL18120)
<b>OSCILLATION ANGLE</b>	3.2° (1.6° LEFT/RIGHT)
<b>OSCILLATIONS PER MINUTE</b>	6,000 – 20,000 OPM
<b>BLADE CHANGE SYSTEM</b>	TOOL-LESS
<b>VIBRATION LEVEL</b>	<b>SANDING:</b> 4.3 M/S <sup>2</sup>   <b>CUTTING:</b> 12.0M/S <sup>2</sup>
<b>VARIABLE SPEED CONTROL</b>	6 STAGE DIAL
<b>WEIGHT (SKIN)</b>	1.4KG
<b>WEIGHT (BL1860B)</b>	2.1KG
<b>DIMENSIONS (LxWxH)</b>	283MM x 80MM x 107MM

## HIGHLIGHTS



### DEPTH GAUGE ATTACHMENT

Attach the optional depth gauge for precise cutting applications. Features vertical and horizontal orientations.




### DUST EXTRACTION ATTACHMENT

The optional dust extraction attachment enables dust collection during messy sanding and cutting applications.



### TOOL-LESS BLADE CHANGE

Features a tool-less blade change system for quick and easy blade changes.



### SLIMLINE GRIP

Features a slim, easy to hold grip measuring just 139mm in circumference.

## FEATURES

**SLIMLINE GRIP:** Slimline grip circumference for unmatched control at just 139mm, delivering superior maneuverability and comfort to tackle any project with precision and ease.

**POWER & EFFICIENCY:** Makita-built brushless motor provides ultimate power, precision, and useability.

**CONSTANT ROTATION CONTROL:** Maintains rotation speeds regardless of load applied to the tool.







**WIDE OSCILLATION ANGLE:** 3.2° total oscillation angle for efficient material removal.

**VARIABLE SPEED:** Variable speed dial ranging from 6,000 – 20,000 OPM to suit a wide variety of applications and material types.

**BLADE COMPATIBILITY:** Accepts OIS (Oscillating Interface System) blade fitment for universal compatibility across the market.

**DURABILITY:** Features eXtreme Protection Technology (XPT) for enhanced dust and water ingress protection in the harshest jobsite environments.



IMAGE	MODEL		BLADE TYPE		
	<b>DTM52</b>				
	<b>DTM53</b>				

### OPTIONAL ACCESSORIES

**1916E4-5**

Depth Gauge Assembly



**1916E5-3**

Dust Extraction Attachment



**RANGE**

Makita Multi Tool Accessories



**197564-4**

18V LXT 5.0Ah Battery & Charger Kit



МАГАЗИН  
БАШ  
ПРОДУКТИ  
ИСТОРА  
РЕШЕНИЯ