

SWA



Characteristics

- Extremely rugged steel bracket with a wide working face
- High corrosion resistance thanks to zinc-plated surface
- Precision-crafted measuring surfaces

Manufacturer

SOLA-Messwerkzeuge GmbH & Co KG
Unteres Tobel 25
6840 Götzis, Austria
T +43 5523 533800
www.sola.at, sola@sola.at

Model	Length	PU	VP	Art. Nr.	EAN
SWA 100	100 x 70 mm	1	○	56112201	9002719020974
SWA 150	150 x 100 mm	1	○	56112301	9002719008231
SWA 200	200 x 130 mm	1	○	56112401	9002719008248
SWA 250	250 x 160 mm	1	○	56112501	9002719008255
SWA 300	300 x 180 mm	1	○	56112601	9002719008262
SWA 400	400 x 230 mm	1	○	56112701	9002719008279
SWA 500	500 x 280 mm	1	○	56112801	9002719008286
SWA 600	600 x 330 mm	1	○	56112901	9002719008293
SWA 750	750 x 375 mm	1	○	56113001	9002719020981
SWA 1000	1000 x 500 mm	1	○	56113101	9002719020998

Technical details

Item description	Locksmith's square
Material	Steel
Surface	polished
Color	galvanized
Special characteristic	Working face
Angular dimension	90°
Width	20 mm, 25 mm, 30 mm
Thickness	0.2 in. (5 mm)

SOLA-Messwerkzeuge GmbH & Co KG
Unteres Tobel 25
6840 Götzis, Austria
T +43 5523 53380-0
sola@sola.at, www.sola.at

SOLA-Messwerkzeuge GmbH & Co. KG
Heuriedweg 69
88131 Lindau, Germany
T +49 8382 28585
sola@sola.at, www.sola.de

SOLA Suisse AG
Grenzstrasse 24
9430 St. Margrethen, Switzerland
T +41 71 740 1616
info@solasuisse.ch
www.solasuisse.ch