

WL S1000



Characteristics

- Daylight-like main light with 3 brightness levels for clear contrast and natural, realistic color rendering
- 1000 lumen SMD LED main light and 200 lumen auxiliary light for bright, even illumination and a precise spotlight
- 180° swivel base for optimal light positioning
- Shock-resistant, rubberized housing with IP54 and IK07 protection
- 2 x 360° rotating hanging hooks and strong holding magnets in base and rear
- Built-in Li-ion battery for up to 7 hours of run time

Manufacturer

SOLA-Messwerkzeuge GmbH & Co KG
Unteres Tobel 25
6840 Götztis, Austria
T +43 5523 533800
www.sola.at, sola@sola.at

Model	PU	VP	Art. Nr.	EAN
WL S1000	1		24240003	9002719047063

Technical details

Item description	Work Light
Operating temperature	0 °C to +25 °C
Protection class	IP54
Power supply	3.7 V (2600 mAh) Li-ion battery
Impact resistance	IK07
Light source	Main light + spot
Luminous flux	180 - 1000 lm
Illuminance	450 - 4000 lx
Beam distance	15 - 60 m



SOLA-Messwerkzeuge
GmbH & Co KG
Unteres Tobel 25
6840 Götztis, Austria
T +43 5523 53380-0
sola@sola.at, www.sola.at

SOLA-Messwerkzeuge
GmbH & Co. KG
Heuriedweg 69
88131 Lindau, Germany
T +49 8382 28585
sola@sola.at, www.sola.de

SOLA Suisse AG
Grenzstrasse 24
9430 St. Margrethen, Switzerland
T +41 71 740 1616
info@solasuisse.ch
www.solasuisse.ch