

WL X1700



Characteristics

- Daylight-like main light with 3 brightness levels for clear contrast and natural, realistic color rendering
- 1700 lumen COB LED main light with wide beam angle for bright, even illumination
- 250° swivel and 310° rotating main light for optimal light positioning
- Shock-resistant, rubberized housing with IP65 and IK07 protection
- Robust retaining clip and powerful holding magnet on the rear
- Built-in Li-ion battery for up to 8 hours of run time

Manufacturer

SOLA-Messwerkzeuge GmbH & Co KG
Unteres Tobel 25
6840 Götzis, Austria
T +43 5523 533800
www.sola.at, sola@sola.at

Model	PU	VP	Art. Nr.	EAN
WL X1700	1		24240004	9002719047070

Technical details

Item description	Work Light
Operating temperature	0 °C to +25 °C
Protection class	IP65
Power supply	3.7 V (5200 mAh) Li-ion battery
Impact resistance	IK07
Light source	Main light
Luminous flux	300 - 1700 lm
Illuminance	480 - 2400 lx
Beam distance	21 - 49 m



SOLA-Messwerkzeuge GmbH & Co KG
Unteres Tobel 25
6840 Götzis, Austria
T +43 5523 53380-0
sola@sola.at, www.sola.at

SOLA-Messwerkzeuge GmbH & Co. KG
Heuriedweg 69
88131 Lindau, Germany
T +49 8382 28585
sola@sola.at, www.sola.de

SOLA Suisse AG
Grenzstrasse 24
9430 St. Margrethen, Switzerland
T +41 71 740 1616
info@solasuisse.ch
www.solasuisse.ch