

WL S1000

Work light

2-in-1



Color rendering
Ra > 80 / > 70



1000 lumens



2-in-1 main light plus spotlight



Main light with 3 brightness levels

Optimal illumination with clear contrasts (6500 K)

Excellent color rendering (main light Ra > 80, spotlight Ra > 70)

180° swivel base



2 × 360° rotating hooks

Impact-resistant housing (IK07)

Charge status and remaining capacity indicator

USB-C

Up to 7 h runtime

IP54 ingress protection rating

Integrated magnets in the base and on the back



Powerful illumination meets precise detail lighting.

The flexible WL S1000 handheld light delivers powerful light for broad-area illumination as well as a precise spotlight for fine detail work. Its 180° swivel base with integrated magnet allows for flexible attachment and precise positioning of the light. Additional magnets on the back and two fold-out, 360° rotating hooks guarantee maximum flexibility for hands-free work at any job site.

Highlights

- Powerful SMD LED technology for bright, even illumination with up to 1,000 lumens
- Spot LED in the lamp head for targeted illumination
- Near-daylight light for clear contrasts and true-to-life detail perception
- Excellent color rendering for natural-looking, true-to-life colors
- Main light with 3 brightness levels for optimal adjustment of light output to different working conditions
- Versatile mounting and positioning options for comfortable, hands-free work
- Powerful lithium-ion rechargeable battery for a runtime of up to 7 hours
- Rugged plastic housing reliably protects against dust, water jets, and drops



The main light provides even illumination, while the spot LED on the lamp head delivers targeted light for inspection and detail work.



The 180° swivel base, two 360° rotating hooks, and integrated mounting magnets allow for flexible attachment and positioning of the light for comfortable, hands-free work.



Ordering information WL S1000
(Item no. 24240003, EAN 9002719047063)

- Delivery contents
- WL S1000
 - USB-C charging cable



Technical data	Main light			Spot
	Low	Medium	High	
Light source	14x 1 W SMD LEDs			1x 5 W SMD LED
Luminous flux	350 lm	500 lm	1000 lm	180 lm
Illuminance	450 lx	1000 lx	1450 lx	4000 lx
Beam distance	15 m	25 m	35 m	60 m
Runtime	4.5 hrs	3.0 hrs	2.5 hrs	7.0 hrs
Color temperature (CCT)	6500 K			6500 K
Color rendering index (CRI)	Ra > 80			Ra > 70
Charging time	4 hrs			
Rechargeable battery	Li-Ion 3.7 V, 2600 mAh			
Protection class	IP54, IK07			
Weight	335 g			