

WL S400

Work light

2-in-1



Color
rendering
Ra ≥ 80 / ≥ 75



400
lumens



2-in-1 main light
plus spotlight



Charge status
and remaining
capacity indicator

USB-C

Main light with 3
brightness levels

180° swivel base




360° rotating hook

Belt clip

Up to 6 h runtime

Integrated magnet



**Compact in size.
Versatile in use.**

The compact WL S400 work light impresses with daylight-white light and high-quality color rendering for precise work. The main light provides even illumination, while the spot LED in the lamp head delivers targeted light for inspection and detail work. With a 180° swivel handle, 360° rotating hook, mounting magnet, and belt clip, the light offers flexible mounting and positioning options for hands-free work.

Highlights

- Main light with powerful COB LED technology for even illumination with a brightness of up to 400 lumens
- Auxiliary light in the lamp head for targeted illumination during inspection and detail work
- Near-daylight light for clear contrasts and true-to-life detail perception
- Outstanding color rendering for natural-looking, true-to-life colors
- Main light with 3 brightness levels for flexible adjustment of light output
- Flexible mounting and positioning options for comfortable, hands-free work
- Powerful lithium-ion rechargeable battery for a runtime of up to 6 hours
- Rugged housing provides protection against dust, water jets, and impacts



The main light provides even illumination, while the spot LED on the lamp head delivers targeted light for inspection and detail work.



The 180° swivel handle, the 360° rotating hook, the integrated mounting magnet, and the belt clip allow for flexible attachment and positioning of the light for comfortable, hands-free work.



Ordering information WL S400
(Item no. 24240002, EAN 9002719047056)

Delivery contents

- WL S400
- USB-C charging cable



Technical data	Main light			Spot
	Low	Medium	High	
Light source	4 W COB LED			2 W SMD LED
Luminous flux	120 lm	200 lm	400 lm	150 lm
Illuminance	200 lx	300 lx	630 lx	630 lx
Beam distance	8 m	12 m	25 m	25 m
Runtime	6.0 hrs	4.0 hrs	2.5 hrs	6.0 hrs
Color temperature (CCT)	6500 K			7000 K
Color rendering index (CRI)	Ra ≥ 80			Ra ≥ 75
Charging time	2.5 hrs			
Rechargeable battery	Li-Po 3.7 V, 1500 mAh			
Protection class	IP65, IK07			
Weight	134 g			