





CYLINDRICAL INSERT NUT

Reduced head - open end

STEEL®



Steel Zincplated 7µ min.



D	 E MIN. mm MAX.	L	d1	d2	 mm	PACKAGING		 (N)	 (N)	 (Nm)	REFERENCE
						Inner	Outer				
M 3	0,5 - 1,5	8,70	4,65	5,40	5,10	500	4.000	2100	3650	1,7	0301203005
M 4	0,5 - 2,0	10,40	6,30	6,70	6,40	500	4.000	3400	7200	2,8	0301204006
M 5	0,5 - 3,0	11,50	7,10	7,90	7,20	500	4.000	5300	9800	5,7	0301205007
M 6	0,5 - 3,0	14,50	9,50	10,20	9,60	500	3.000	6500	19100	6,5	0301206009
M 8	0,5 - 3,0	16,50	10,50	11,30	10,60	250	1.500	8350	29800	8,6	0301208011

For drills in inches.

D	 E MIN. mm MAX.	L	d1	d2	 mm	PACKAGING		 (N)	 (N)	 (Nm)	REFERENCE
						Inner	Outer				
M 4	0,5 - 2,0	10,00	5,90	7,00	6,00	500	4.000	3400	7200	2,8	0301204005
M 5	0,5 - 3,0	12,00	6,90	8,00	7,00	500	4.000	5300	9800	5,7	0301205006
M 6	0,5 - 3,0	15,00	8,90	10,00	9,00	500	3.000	6500	19100	6,5	0301206008
M 8	0,5 - 3,0	16,00	10,90	12,00	11,00	250	1.500	8350	29800	8,6	0301208010

For drills in mm.

