



DIN EN 24 231


HOBBY NO/CS/WS
code 212 XXX

STANDARD HSS
code 242 XXX

STANDARD HSS
code 252 XXX

STANDARD HSS
code 272 XXX

**Závitové kruhové
čelisti**
Circular dies
Schneideisen
Плшки



G(BSP)

Trubkový závit DIN ISO 228
Pipe thread DIN ISO 228
Rohrgewinde DIN ISO 228
Трубная резьба DIN ISO 228

Licování: třída A / Tolerance: class A /
Toleranz: Klasse A / Подгонка: класс А



1,5P

z/1"	P	ØD	h	S		code*)
G 1/16"	28	0,907	25	9	4	7,62 XXX 116
G 1/8"	28	0,907	30	11	4	9,62 XXX 180
G 1/4"	19	1,337	38	10	5	13,03 XXX 140
G 3/8"	19	1,337	45	14	5	16,54 XXX 380
G 1/2"	14	1,814	45	14	6	20,81 XXX 120
G 5/8"	14	1,814	55	16	6	22,77 XXX 580
G 3/4"	14	1,814	55	16	6	26,30 XXX 340
G 7/8"	14	1,814	65	18	6	30,06 XXX 780
G 1"	11	2,309	65	18	8	33,07 XXX 100
G 1 1/8"	11	2,309	75	20	8	37,72 XXX 118
G 1 1/4"	11	2,309	75	20	9	41,73 XXX 114
G 1 3/8"	11	2,309	90	22	8	44,14 XXX 138
G 1 1/2"	11	2,309	90	22	8	47,62 XXX 112
G 1 3/4"	11	2,309	105	22	8	53,57 XXX 134
G 2"	11	2,309	105	22	8	59,43 XXX 200
G 2 1/4"	11	2,309	120	22	8	65,49 XXX 214
G 2 1/2"	11	2,309	120	22	8	74,97 XXX 212
G 2 3/4"	11	2,309	120	22	8	81,32 XXX 234
G 3"	11	2,309	150	25	10	87,67 XXX 300
G 3 1/4"	11	2,309	150	25	10	91,50 XXX 314
G 3 1/2"	11	2,309	150	25	10	100,11 XXX 312
G 4"	11	2,309	180	25	10	112,81 XXX 400

*) 212 XXX - NO / CS / WS do G 2" / to G 2" / bis G 2" / до G 2"

*) 242 XXX - HSS

*) 252 XXX - HSS LH

*) 272 XXX - HSS s lamačem třísek do G 2" / with spiral point to G 2" / mit Schälanschnitt bis G 2" / с ломателем стружек до G 2"

Materiál: NO; HSS
Provedení: závit lapovaný
do G 3/4"
Závit: pravý, levý

Material: CS; HSS
Execution: lapped thread to
G 3/4"
Thread: right-hand, left-hand

Werkstoff: WS-Werkzeugstahl;
HSS
Ausführung: geläpptes
Gewinde bis G 3/4"
Gewinde: rechts, links

Material: NO-инструментальная сталь; HSS
Изготовлено: резьба шлицованная до G 3/4"
Резьба: правая, левая

DIN EN 24 231

PROFI HSS Ms
code 282 XXX

PROFI HSSE
code 292 XXX

PROFI HSSE VA
code 293 XXX

PROFI HSSE VA-NT
code 296 XXX

z/1"	P	ØD	h	S		code*)
G 1/16"	28	0,907	25	9	4	7,62 XXX 116
G 1/8"	28	0,907	30	11	4	9,62 XXX 180
G 1/4"	19	1,337	38	10	5	13,03 XXX 140
G 3/8"	19	1,337	45	14	5	16,54 XXX 380
G 1/2"	14	1,814	45	14	6	20,81 XXX 120
G 5/8"	14	1,814	55	16	6	22,77 XXX 580
G 3/4"	14	1,814	55	16	6	26,30 XXX 340
G 7/8"	14	1,814	65	18	6	30,06 XXX 780
G 1"	11	2,309	65	18	8	33,07 XXX 100
G 1 1/8"	11	2,309	75	20	8	37,72 XXX 118
G 1 1/4"	11	2,309	75	20	9	41,73 XXX 114
G 1 3/8"	11	2,309	90	22	8	44,14 XXX 138
G 1 1/2"	11	2,309	90	22	8	47,62 XXX 112
G 1 3/4"	11	2,309	105	22	8	53,57 XXX 134
G 2"	11	2,309	105	22	8	59,43 XXX 200

*) 282 XXX - HSS Ms - na mosaz / brass / Messing / латунь

*) 292 XXX - HSSE

*) 293 XXX - HSSE VA - na nerez / stainless steel / Rostfreistähle / нержавејка

*) 296 XXX - HSSE VA-NT - na nerez - nitridace / stainless steel - nitration / Rostfreistähle - Nitrierung / нержавејка - нитридование



**BUČOVICE
TOOLS a.s.**

Materiál: HSS; HSSE, HSSE
VA-NT - dle požadavku
Provedení: závit lapovaný
do G 3/4"
Závit: pravý

Material: HSS; HSSE, HSSE
VA-NT - on request
Execution: lapped thread to
G 3/4"
Thread: right-hand

Werkstoff: HSS; HSSE,
HSSE VA-NT - nach dem
Anspruch
Ausführung: geläpptes
Gewinde bis G 3/4"
Gewinde: rechts

Material: HSS; HSSE,
HSSE VA-NT - по заказу
Изготовлено: резьба
шлифованная до G 3/4"
Резьба: правая

42 G(BSP)