

# AIRONE 300 N

Hoists with telescopic arm – capacity 300 kg

## Standard Equipment


- ✓ Work positioning lever
- ✓ IP67 plug
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton IP65 1-m pendant control
- ✓ Self-braking motor with magnetic device



## Optional Accessories

- ✓ Prop
- ✓ Ballast container

## Applications

The special machine configuration makes it easy to install thanks to better weight distribution for the operator. The raised loading point simplifies the passing of materials through windows. Airone 300 N have an extensible arm up to 1100 mm. Maximum capacity remains unchanged for the entire extension so bulky material can be lifted without the risk of striking the structures.

-  300 kg
-  19 m/min
-  30 m



## Column prop for Airone 300 N

The Airone 300 New has the possibility of a specific optional column prop for hoists with max. capacity of 300 kg.

AIRONE 300 N		
Maximum capacity	kg	300
Av. full load lifting speed	m/min	19
Max. working height	m	30
Ø steel rope	mm	5
Rope length	m	31
Electric power supply	V / Hz	230 / 50 Sph
Motor power rate	kW	1.1
Motor speed	rpm	1320
Running current	A	10
Machine weight	kg	55
SPL in operator's position	dB(A)	72
Dimensions w/l/h	mm	350/820/550
Packing dimensions w/l/h	mm	330/850(1100)/625