

# Schalungsbohrer HSS

Form Work Auger Drill Bit HSS

HSS

90000



Art.-Gruppe 64  
Article Group 64

Material HSS

Einzel-SB/Single Packaging DIY

Ø mm	L	Ø Schaft Ø Shank	€/Stk. €/Pc.	Art.-Nr. Art.-No.
6	400	5		906400
6	600	5		906600
8	400	6		908400
8	600	6		908600
8	800	6		908800
10	400	8		910400
10	600	8		910600
10	800	8		910800
12	400	8		912400
12	600	8		912600
12	800	8		912800
14	400	8		914400
14	600	8		914600
14	800	8		914800
16	400	10		916400
16	600	10		916600
16	800	10		916800
18	400	10		918400
18	600	10		918600
18	800	10		918800
20	400	10		920400
20	600	10		920600
20	800	10		920800

Einzel-SB/Single Packaging DIY

Ø mm	L	Ø Schaft Ø Shank	€/Stk. €/Pc.	Art.-Nr. Art.-No.
22	400	10		922400
22	600	10		922600
22	800	10		922800
24	400	11		924400
24	600	11		924600
24	800	11		924800
26	400	11		926400
26	600	11		926600
26	800	11		926800
28	400	11		928400
28	600	11		928600
28	800	11		928800
30	400	11		930400
30	600	11		930600
30	800	11		930800

Andere Abmessungen auf Anfrage/

Additional dimensions upon request



- ▶ Ausführung entsprechend den Sicherheitsvorschriften der Berufsgenossenschaft nach DIN Entwurf 7490
- ▶ Bohrerteil und Schaft sind durch ein Feingewinde verbunden und zusätzlich verklebt, dadurch optimale Rundlaufgenauigkeit
- ▶ Hohe Haltbarkeit und Bruchsicherheit selbst bei stärkster Belastung
- ▶ Großer Spänekanal bis zum Spirauslauf für schnelle Spanabfuhr
- ▶ Der abgesetzte Schaft verhindert ein Klemmen im Bohrloch
- ▶ Mit Zylinderschaft für Handbohrmaschinen
- ▶ Für Schalungen, Bleche, Bretter, Balken usw.
- ▶ Bohrungen für Spannschrauben und -drähte in einem Arbeitsgang
- ▶ Conformity to the safety requirements of the German employers liability insurance association according to the draft standard DIN 7490
- ▶ Fine thread connection between bit and shank, the two pieces are also glued to ensure concentricity accuracy
- ▶ High durability even under high load
- ▶ Fast chip removal because of big flute design
- ▶ Reduced shank avoids clamping in the bore hole
- ▶ With straight shank for handle drills
- ▶ Designed to drill: Board, Beam, Shuttering, Metal Sheet
- ▶ Bore hole for bottle screw and bracing wire in one operation

# Installationsbohrer HSS mit 4 Nuten

Form Work Auger Drill Bit HSS with SDS – Plus Shank

SDS-plus

87000



Art.-Gruppe 17  
Article Group 17

Material HSS

Einzel-SB/Single Packaging DIY

Ø mm	L	€/Stk. €/Pc.	Art.-Nr. Art.-No.
10	400		8710400
10	600		8710600
12	400		8712400
12	600		8712600
14	400		8714400
14	600		8714600

Einzel-SB/Single Packaging DIY

Ø mm	L	€/Stk. €/Pc.	Art.-Nr. Art.-No.
16	400		8716400
16	600		8716600
18	400		8718400
18	600		8718600
20	400		8720400
20	600		8720600

Einzel-SB/Single Packaging DIY

Ø mm	L	€/Stk. €/Pc.	Art.-Nr. Art.-No.
22	400		8722400
22	600		8722600
24	400		8724400
24	600		8724600

Andere Abmessungen auf Anfrage/

Additional dimensions upon request