





T 250 ECO-2

The compact circular saw bench for quick and easy wood working

sturdy underframe

practical cross-, mitre fence and quick adjustable parallel fence with lens

infinitely variable height- and inclined adjustment of saw blade

МАГАЗИН: гр. Варна; ул. "Струга" № 23, тел.: 052/64 30 30; факс: 052/64 30 35, моб.: +359 88 925 2963, email: info@bashmajstora.com СЕРВИЗ: гр. Варна; ул. "Струга" № 25, тел.: 052/64 30 30; факс: 052/64 30 35, моб.: +359 88 806 2122, email: service@ bashmajstora.com







Circular saw bench **ATIKA T 250 ECO-2** - compact construction, many adjustment possibilities and low weight. The perfect assistant for quick wood working.

## **Equipment:**

- Ø 250 mm saw blade with 24 hard metal tipped teeth infinitely variable adjustable in height up to approx. 85 mm and in bevel up to 45° with easy hand wheel
- · sturdy underframe ensures a high stability
- practical cross- and mitre fence adjustable up to 60°
- · steady saw table made of steel guarantees a long service life
- quick adjustable parallel fence with lense, guided on a guide bar with mm-scala
- 2 connections for dust suction directly at saw blade guard and at housing













|   | Circular saw bench                                                       | T 250 ECO-2   |
|---|--------------------------------------------------------------------------|---------------|
|   | Order-no.                                                                | 302644        |
| ч | AC-motor                                                                 | 230 V ~ 50 Hz |
|   | Power P <sub>1</sub> (S1)                                                | 1800 W        |
|   | Idle speed                                                               | 5000 rpm      |
|   | Fuse                                                                     | 10 A inert    |
|   | Hard metal saw blade                                                     | Ø 250 mm      |
|   | Saw blade bore                                                           | Ø 30 mm       |
|   | Number of teeth                                                          | 24            |
|   | Cutting height at 90°                                                    | max. 85 mm    |
|   | Incline adjustment (swivelling range)                                    | 0° - 45°      |
|   | Cross- and mitre fence                                                   | 0° - 60°      |
|   | Table height (with underframe)                                           | 825 mm        |
|   | Sound power level at work L <sub>wA</sub>                                | 104 dB (A)    |
|   | Measurement uncertainty K                                                | 3 dB(A)       |
|   | Sound pressure level at work L <sub>PA</sub>                             | 91 dB (A)     |
|   | Motor overload protection switch                                         | <b>√</b> .    |
|   | Connection for dust suction                                              | <b>√</b>      |
|   | Incl. push stick, tools, parallel stop with lens, cross- and mitre fence | <b>√</b>      |
|   | Weight approx.                                                           | 19 kg         |
|   |                                                                          |               |