Laserliner®

AutoLine-Laser 3D Set 300 cm

Three-dimensional laser with a horizontal and two vertical 360° laser circles



- PowerBright⁺ laser with 3 extremely bright 360 degree laser lines
- Straight forward plumb function using laser
- Automatic Level: automatic alignment by virtue of a magnetic pendulum system.
 - Tilt mode is an additional feature that
 - Optimised for work close to the ceiling
 - Out-Of-Level: is indicated by optical levelling range.
 - **RX-Ready:** The integrated hand receiver mode detects the laser lines with the optional laser receiver RX up to a max. of 50 m radius – ideal for all interior and exterior applications.
 - **Transport Lock**

Compact Tripod 300 cm

- - (rubber steel tips) facilitate adaptation to different
 - 5/8" thread adapter



- - permits gradients to be laid out.
 - signals when the unit is outside its self-

- High-quality, very compact crank tripod made of aluminium
 - Special combination feet



Automatic Level



Pendulum can be locked for protection during transport



Optional: laser receiver (max. 50 m radius)

ARTICLE	ARTICLE NO	EAN-CODE	PU
AutoLine-Laser 3D Set 300 cm	036.201A	4 021563 687589	2





















TECHNICAL DATA

ACCURACY 2 mm / 10 m

SELF-LEVELLING RANGE ± 2,5°

OPERATING RANGE

(depending on room illumination) 20 m

LASER WAVELENGTH 640 nm

LASER

line lasers, class 2M < 5 mW

POWER SUPPLY

4 x 1,5V (type AA, LR6)

OPERATING TIME

with 3 laser levels: approx. 6 hours with 2 laser levels: approx. 10 hours with 1 laser level: approx. 25 hours

WORKING TEMPERATURE 0°C ... +50°C

STORAGE TEMPERATURE -10°C ... +70°C

WATER AND DUST PROTECTION IP 54 WEIGHT ALL 3D incl. batteries 820 g

DIMENSIONS ALL 3D 85 x 130 x 160 mm (W x H x D)







AutoLine-Laser 3D set 300 cm

inclusive AutoLine-Laser 3D

- + softbag
- + batteries

inclusive Compact Tripod 300 cm + softbag

Packing dimension (W \times H \times D) 220 x 1065 x 215 mm

Weight (complete set)