



МАГАЗИНИ
БАШ МАЙСТОРА[®]
ПРОФЕСИОНАЛНИ РЕШЕНИЯ

Makita[®]

Makita[®]

500°C Heat Gun

HG5030K





Product Objectives

- Designed for stripping paint, soldering pipes, shrinking PVC, welding and bending plastic as well as general drying and thawing purposes
- Develop a newly designed heat gun with 2 stage air flow and temperate settings
- The HG5030K replaces the HG5010





Product Overview

Compatible with various accessories

Self standing design

Overheat protection

2 stage slide switch

Compact and light weight





Product Specification Sheet



- **Compatible with various accessories** – ability to perform a wide range of tasks such as stripping paint, soldering pipes and shrinking PVC with a variety of accessories (see page 10 for complete list)
- **Overheat protection** – prevent the tool from damage due to overheating
- **Compact and lightweight** – for easy handling and use at 233mm in length and 0.56kg in weight
- **Self standing design** – supports gun in up position for operator convenience during application and nozzle changes
- **2 stage slide switch** – easy to operate slide switch, adjusts air flow and temperature

Air temperature	Stage 1: 350°C Stage 2: 500°C
Air volume	Stage 1: 300L/min Stage 2: 500L/min
Continuous rating input	1,600W
Overall length	233mm
Net weight	0.56kg
Power supply cord	2.0m



Advantages

Power



Delivers max. air temperatures of 500°C
and 500L/min air volume

Convenience



Self standing design for comfortable use

Control



Easy to operate 2 stage slide switch
adjusting both temperature and airflow



Versatile



Various optional accessories available for a
wide variety of tasks



Product Replacement

	HG5010 - Discontinued	HG5030K
		
Air temperature	Stage 1: 300°C Stage 2: 500°C	Stage 1: 350°C Stage 2: 500°C
Air volume	Stage 1: 240L/min Stage 2: 450L/min	Stage 1: 300L/min Stage 2: 500L/min
Continuous rating input	1,400W	1,600W
Overall length	235mm	233mm
Net weight	0.65kg	0.56kg
Power supply cord	2.0m	2.0m



Our Range


Makita[®]

	HG5030K	HG6020	HG6020KIT	HG6500
				
Air temperature	Hi: 500°C Lo: 350°C	50-600°C	50-600°C	70-650°C
Air volume	Hi: 500L/min Lo: 300L/min	150-500L/min	150-500L/min	Hi: 550L/min Lo: 280L/min
Continuous rating input	1,600W	2,000W	2,000W	2,000W
Overall length	233mm	263mm	263mm	262mm
Net weight	0.56kg	0.85kg	0.85kg	0.92kg
Power supply cord	2.0m	2.0m	2.0m	2.0m






Accessories

Standard Accessories

	-	Case
---	---	------

Optional Accessories

	PR00000028	Glass protection nozzle
	PR00000029	Wide-slot nozzle
	PR00000030	Reflector nozzle
	PR00000031	Reduction nozzle
	PR00000032	Overlap welding nozzle

Optional Accessories

	PR00000033	Solder sleeves reflector
	PR00000034	Welding nozzle
	PR00000035	Pressure roller
	PR00000036 PR00000037 PR00000038	ABS – Welding rods HDPE – Welding rods PP – Welding rods
	PR00000039	Speed welding nozzle
	PR00000040	Scraper
	PR00000041	Scraper set
	PR00000042	Scraper