

Maschinen Forstnerbohrer

Forstner Drill Bit

6,35 mm (1/4") 6-kant Aufnahme

with 6,35 mm (1/4") Hexagonal Shank



33400



Art.-Gruppe 62
Article Group 62

Einzel-SB/Single Packaging DIY

Ø mm	L	€/Stk. €/Pc.	Art.-Nr. Art.-No.
10	90		33 410
12	90		33 412
14	90		33 414
15	90		33 415
16	90		33 416
18	90		33 418
20	90		33 420
22	90		33 422
24	90		33 424

Einzel-SB/Single Packaging DIY

Ø mm	L	€/Stk. €/Pc.	Art.-Nr. Art.-No.
25	90		33 425
26	90		33 426
27	90		33 427
28	90		33 428
30	90		33 430
32	90		33 432
34	90		33 434
35	90		33 435


- ▶ Punktgenaue, splitterfreie Bohrungen
- ▶ Mit Zentrierspitze, 2 Hauptschneiden und Umfangschiene (nach DIN 7483G)
- ▶ Präzisionsschliff für saubere Bohrungen
- ▶ Rechtsschneidend
- ▶ Zur Verwendung in Akkubohr- und Handbohrmaschinen
- ▶ Für Weichholz und furnierte Platten

- ▶ For exact and splitterfree drilling
- ▶ With center point, two cutting edges and circumferential blade (to DIN 7483G)
- ▶ Grinded for accurate bore holes
- ▶ To be used in handle and cordless drills
- ▶ Designed to drill: Soft wood and veneered wooden board

Maschinen Forstnerbohrer

Forstner Drill Bit

33000



Art.-Gruppe 62
Article Group 62

Drehzahlempfehlungen für Forstnerbohrer
Recommended Speeds for Super Forstner Bit

	Ø mm	U/min. ca. approx. rpm
Weichholz/ Soft Wood	10 – 20	1500 – 1200
	25 – 30	1200 – 1000
	35 – 40	1000 – 800
	45 – 50	800 – 600
Hartholz/ Hard Wood	10 – 20	1200 – 1000
	25 – 30	1000 – 800
	35 – 40	800 – 600
	45 – 50	600 – 400

Zahnung
Toothed

Ø mm	Zahnung Toothed
10 – 18	1
20 – 34	2
35 – 60	3

Einzel in SB Verpackungen
Single Packaging in DIY-Packaging



- ▶ Punktgenaue, splitterfreie Bohrungen
- ▶ Mit Zentrierspitze, 2 Hauptschneiden und Umfangschiene (nach DIN 7483G)
- ▶ Präzisionsschliff für saubere Bohrungen
- ▶ Zylindrisch abgesetzter Schaft
- ▶ Zur Verwendung in Handbohrmaschinen
- ▶ Empfohlene Drehzahl 400 – 1400 U/min (je nach Ø)
- ▶ Für Weichholz, furnierte Platten

- ▶ For exact and splitterfree drilling
- ▶ With center point, two cutting edges and circumferential blade (to DIN 7483G)
- ▶ Grinded for accurate bore holes
- ▶ Reduced straight shank
- ▶ To be used in handle drill
- ▶ Recommended drilling speed: 400 – 1.400 rpm (depends on Ø)
- ▶ Designed to drill: Soft wood and veneered wooden board

Einzel-SB/Single Packaging DIY

Ø mm	Ø Schaft Ø Shank	L	€/Stk. €/Pc.	Art.-Nr. Art.-No.
10	8	90		33 010
12	8	90		33 012
14	8	90		33 014
15	8	90		33 015
16	8	90		33 016
18	8	90		33 018
20	8	90		33 020
22	8	90		33 022
24	8	90		33 024
25	8	90		33 025
26	8	90		33 026
27	8	90		33 027

Einzel-SB/Single Packaging DIY

Ø mm	Ø Schaft Ø Shank	L	€/Stk. €/Pc.	Art.-Nr. Art.-No.
28	8	90		33 028
30	8	90		33 030
32	10	90		33 032
34	10	90		33 034
35	10	90		33 035
36	10	90		33 036
38	10	90		33 038
40	10	90		33 040
45	10	90		33 045
50	10	90		33 050
55	10	90		33 055
60	10	90		33 060

SORTIMENTE / SETS
ab Seite P 259 / from page 259