

Laserliner®

ActiveFinder XP



Professional voltage testing
of electrical wiring and systems
– in handy pen format

Rev.0317



– **Contactless detection** of live lines from 12 V AC to 1000 V AC

– **Locates electrical voltages** in cables, sockets, bulb sockets, fuses as well as control cabinet and system components.

– **Finds breaks** in wires and cables

– **CAT IV - 1000V** – can be used for measurements throughout building installations

– **Extremely high sensitivity** for tracing lines at great depths (Zoom)

– **Clearly visible LED multi-colour signalling** for indicating electrical voltages and statuses


– Reliable status indication by additional **acoustic signalling with vibration function** even in noisy environments

– **Super-bright, integrated flashlight** with separate ON/OFF button

– **Additional LED light** for illuminating the working area

– **Compact design** with convenient clip, practical for shirt pockets and tool boxes

– Rugged, impact-resistant waterproof housing



Extremely high sensitivity (Zoom)

Super-bright flashlight

TECHNICAL DATA

INDICATOR LED

VOLTAGE RANGE

12 V/AC ~ 1000 V/AC
Frequency 50 ... 60Hz

OVERVOLTAGE CATEGORY

CAT IV - 1000V (non-condensing)
Pollution degree 2

DEGREE OF PROTECTION IP67

FLASHLIGHT

White-light LED (exempt group)

POWER SUPPLY

2 x 1.5 AAA (NEDA 24A/IEC LR 03)

OPERATING CONDITIONS 0 ... 50°C,
Max. humidity 80% rH, no condensation,
max. altitude 2000 m

STORAGE CONDITIONS -10 ... 60°C,
Max. humidity 80% rH

DIMENSIONS (W x H x D)
160 x 24 x 30 mm

WEIGHT (incl. batteries) 66 g



ActiveFinder XP

inclusive softbag

+ batteries (2 x 1.5 AAA)

Packing dimension (W x H x D)

–

ARTICLE	ARTICLE NO	EAN-CODE	PU
ActiveFinder XP	083.013A	4 021563 698905	5

CAT IV
1000V

2x
AAA

IP 67

AutoSound

SOFT