

# BRUSHLESS Premium power & runtime

Our Premium Brushless range is for those who lead the pack seeking industrial quality without compromise. LXT® Premium Brushless tools put you ahead of the game with market leading innovation, maximum power and the ultimate in endurance that 18V has to offer.



## **Product Objectives**

- 8
- Designed to suit the needs of fabricators, engineers, welders and stone masons.
- Develop an 18V angle grinder with a variable speed function which allows users to select the optimum speed for the accessory and the application





#### **Product Overview**



### **Product Specification Sheet**

#### DGA511 - 18V Brushless 125mm (5") Slide Switch Angle Grinder



Wheel diameter	125mm (5")
No load speed	3,000 - 8,500rpm
Overall length	382mm
Skin weight	2.5kg
Weight (with battery)	3.1kg
Voltage	18V

- Automatic torque drive automatically adjusts speed and torque during operation for optimum performance
- Soft start slowly increases speed to full rpm for safe and smooth operation
- **Anti-kickback** turns the motor off if the rotation of the wheel is suddenly forced to stop preventing the tool from kicking backwards
- Anti-restart tool will not start if switch is engaged when a battery is installed. Switch must first return to the off position
- **Variable speed** dial allows the rpm of the grinder to controlled at a range between 3,000 and 8,500rpm
- **XPT eXtreme Protection Technology** for use in outdoor applications or harsh environments, protection from dust and moisture is enhanced
- **BL Brushless Motor** efficient energy production enabling lower heat production and increased work on a single charge

#### **Product Overview**



### **Product Specification Sheet**

#### DGA517 - 18V Brushless 125mm (5") Paddle Switch Angle Grinder



Wheel diameter	125mm (5")
No load speed	3,000 - 8,500rpm
Overall length	382mm
Skin weight	2.5kg
Weight (with battery)	3.1kg
Voltage	18V

- Automatic torque drive automatically adjusts speed and torque during operation for optimum performance
- Soft start slowly increases speed to full rpm for safe and smooth operation
- Anti-kickback turns the motor off if the rotation of the wheel is suddenly forced to stop preventing the tool from kicking backwards
- Anti-restart tool will not start if switch is engaged when a battery is installed. Switch must first return to the off position
- **Variable speed** dial allows the rpm of the grinder to controlled at a range between 3,000 and 8,500rpm
- XPT eXtreme Protection Technology for use in outdoor applications or harsh environments, protection from dust and moisture is enhanced
- **BL Brushless Motor** efficient energy production enabling lower heat production and increased work on a single charge
- Electric brake quickly and smoothly stops the grinding disc for safe and efficient operation

# Advantages



#### **Control**



Variable speed dial allows optimum control for precise material removal

# Safety



Soft start, Anti-kickback and anti-restart

#### **Power**



Automatic torque drive increases torque to power though tough cuts

#### **Innovation**



High powered Brushless motor provides high power and improved runtimes

# 125mm (5") Grinder Features



	DGA504	DGA505	DGA506	DGA508	DGA511	DGA517
		The state of the s				
Switch type	Slide	Paddle	Slide	Paddle	Slide	Paddle
Anti-restart	A CAR				$\checkmark$	$\checkmark$
Soft start			WHI.	<b>√</b>	$\checkmark$	$\checkmark$
Automatic torque drive		160	N.	<b>√</b>	<b>√</b>	$\checkmark$
Anti-kickback		08	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$
Electric brake	X	X	<b>√</b>	<b>√</b>	X	<b>√</b>
Variable speed	X	X	X	X	$\checkmark$	$\checkmark$

# Our Range



	DGA452	DGA504	DGA505	DGA506	DGA508	DGA511	DGA517	DGA700	DGA900
Wheel diameter	115mm (4-1/2")	125mm (5")	125mm (5")	180mm (7")	230mm (9")				
No load speed	10,000rpm	8,500rpm	8,500rpm	8,500rpm	8,500rpm	3,000 - 8,500rpm	3,000 - 8,500rpm	7,800rpm	6,000rpm
Overall length	317mm	362mm	362mm	362mm	362mm	382mm	382mm	499mm	499mm
Skin weight	1.3kg	2.0kg	2.0kg	2.0kg	2.0kg	2.5kg	2.5kg	4.6kg	4.8kg
Weight (with battery)	1.9kg	2.6kg	2.6kg	2.6kg	2.6kg	3.1kg	3.1kg	6.0kg	6.2kg
Voltage	18V	18V	18V	18V	18V	18V	18V	36V (18Vx2)	36V (18Vx2)

# Accessories



Standard Accessories					
	A-80656	125mm Inox Grinding wheel			
Thakita.	153489-2	Side grip			
•	782423-1	Lock nut wrench			
<b>O</b>	224554-1	Lock nut			
0	224314-5	Flange			
	135108-2	Tool-less wheel guard			

Optional accessories	s	
Trackiti  Water  Agents  Trackiti  T	B-35449-10 D-20432-10 B-38489-40 D-20323-5	Metal – Cutting and Grinding 125 x 1.6 x 22.23 (10PK) 125 x 2.5 x 22.23 (10PK) 125 x 3.2 x 22.23 (40PK) 125 x 6 x 22.23 (5PK)
Traketa	B-46981-10 B-18150-10 D- 20535-12 B-27121-5	Inox – Cutting and Grinding 125 x 0.8 x 22.23 (10PK) 125 x 1 x 22.23 (10PK) 125 x 1.2 x 22.23 (12PK) 125 x 6 x 22.23 (5PK)

Optional accessories					
Trakita  Trakita  Trakita  Trakita  Trakita  Trakita  Trakita  Trakita	B-22171-20 B-22187-20 B-22193-20 B-22202-20	Flexible Grinding Wheels – Metal  125 x 3 x 22.23 AC36 (20PK)  125 x 3 x 22.23 AC46 (20PK)  125 x 3 x 22.23 AC60 (20PK)  125 x 3 x 22.23 AC80 (20PK)			
Trakta	B-22414-20 B-22420-20 B-22436-20 B-22442-20	Flexible Grinding Wheels - Inox 125 x 3 x 22.23 WA36 (20PK) 125 x 3 x 22.23 WA46 (20PK) 125 x 3 x 22.23 WA60 (20PK) 125 x 3 x 22.23 WA80 (20PK)			
Tractice  When the state of the	D-20482-10 D-20373-5	Masonry – Cutting and Grinding 125 x 3 x 22.23 (10PK) 125 x 6 x 22.23 (5PK)			
Total Indiana Control of the Control	B-46333	Ultra Thin Diamond Blade – Porcelain 125 x 1.4 x 22.23			
	122688-7	125mm Wheel guard for cutting discs			
Stakite Stakite	196845-3	125mm Dust collecting wheel guard			