

Laserliner®

DistanceMaster Compact Plus




Laser distance meter with Bluetooth interface and colour display



3ev.0316





- Point-precise measuring with laser to determine lengths exactly
- The area and volume functions permit the acquisition of room sizes, for example to calculate material quantities
- Bluetooth interface for measurement data transfer
- Measured value memory for 10 entries
- Measuring accuracy up to 40 m: ± 2 mm*
- Inside measurement range: 0,1 m to 40 m
- 2 selectable measurement reference points: front and rear
- Min/Max function to determine diagonals, verticals and horizontals
- Illuminated 3-line colour LCD
- Sturdy, ergonomically designed, rubberised casing

TECHNICAL DATA

ACCURACY ± 2 mm (typical)*

MEASUREMENT RANGE max. 40 m

MINIMAL RANGE 0,1 m

LASER Class 2 < 1mW

LASER WAVELENGTH 650 nm

OPERATING TEMPERATURE -10°C ... 40°C

STORAGE TEMPERATURE -20°C ... 70°C

UNIT (selectable) m / ft / inch /

AUTOMATIC SWITCH-OFF

30 sec laser / 10 min device

FUNCTIONS

distances, areas, volumes, min/max/duration measurement

POWER SUPPLY

Batteries 2 x 1,5 V type AAA

 $\textbf{DIMENSIONS} \; (\mathsf{W} \; \mathsf{X} \; \mathsf{H} \; \mathsf{X} \; \mathsf{D})$

43 x 110 x 27 mm

WEIGHT with batteries 100 g

See operating instructions for specific accuracies



ARTICLE	ARTICLE NO	EAN-CODE	PU
DistanceMaster Compact Plus	080.938A	4 021563 694211	5

















DistanceMaster Compact Plus

inclusive softbag + batteries (2 x 1,5 V Typ AAA)

Packaging dimension (W x H x D)