

Laserliner

EasyCross-Laser Green



Green cross-line laser for height transmission and alignment

Rev17W50





- **Green laser technology**
- Extremely bright green laser cross at front in the **DLD design achieves high-quality lines** as well as a clean and clear and therefore easily visible line image.
- Ideal for aligning tiles, wallpaper, pictures, etc.
- **Automatic Level:** automatic alignment by virtue of a magnetic pendulum system.
- **Additional slope mode** to align angled surfaces.
- **Out-Of-Level:** is indicated by optical signals when the unit is outside its self-levelling range.
- **Transport Lock:** a pendulum lock protects unit during transport.
- Green laser technology with 0°C...50°C temperature range.

TECHNICAL DATA

SELF-LEVELLING RANGE ± 3°
ACCURACY ± 0,5 mm / m
LEVELLING automatic
OPERATION RANGE (depending on room illumination) 15 m
LASER WAVELENGTH 515 nm
LASER CLASS 2 / < 1 mW
POWER SUPPLY 3 x 1,5V alkaline batteries (type AAA, LR6)
OPERATING TIME 9 Std. (alkaline batteries)
OPERATING CONDITIONS 0...50°C, max. humidity 80% rH, no condensation, max. working altitude 4000 m above sea level
STORAGE CONDITIONS -10°C...70°C, max. humidity 80% rH
DIMENSIONS (W x H x D) 61 x 72 x 62 mm
WEIGHT (incl. batteries) 202 g

1HG 1VG



Automatic Level



ON/OFF button and laser flash when levelling is disabled



1/4"-threads



EasyCross-Laser Green
+ batteries

Packing dimension (W x H x D)
110 x 235 x 80 mm

ARTICLE	ARTICLE NO	EAN-CODE	PU
EasyCross-Laser Green	081.080A	4 021563 703418	5

