



**Laserliner®**

**CompactCube-Laser 3**



Automatic cross-line laser  
 with lateral 90° laser  
 and slope function

Rev.0317




- **PowerBright-Laser:** Special high-performance laser diodes project extremely visible laser lines.
- This unit produces **3 very visible laser lines** which make it outstanding for the alignment of tiles, wall studding, windows, doors, etc.
- The **2 vertical lines** are aligned at right angles to one another.
- **Automatic Level:** automatic alignment by virtue of a magnetic pendulum system.
- **Individually switchable** laser lines
- **Additional slope mode** to align angled surfaces.
- **Out-Of-Level:** is indicated by optical signals when the unit is outside its self-levelling range.
- **Transport lock:** A pendulum lock protects unit during transport.
- **Small, compact design** – fits in any toolbox
- Sturdy, ergonomically designed, **rubberised** casing

**TECHNICAL DATA**

<b>SELF-LEVELLING RANGE</b> ± 3°
<b>ACCURACY</b> ± 0,5 mm / m
<b>LEVELLING</b> automatic
<b>OPERATING RANGE</b> (depending on brightness of area) 15 m
<b>LASER WAVELENGTH</b> 635 nm
<b>LASER CLASS</b> 2 / < 1 mW
<b>POWER SUPPLY</b> 3 x 1.5 V alkaline batteries (type AAA, LR6)
<b>OPERATING TIME</b> with laser cross at front: approx. 20 hours with all laser lines: approx. 9 hours
<b>WORKING TEMPERATURE</b> 0°C ... +40°C
<b>STORAGE TEMPERATURE</b> -10°C ... +70°C
<b>DIMENSIONS (W x H x D)</b> 69 x 69 x 65 mm
<b>WEIGHT</b> (incl. batteries) 285 g

1H 2V



Automatic Level



Fits in any toolbox



1/4"-threads



**CompactCube-Laser 3**  
 + batteries

**Packaging dimension (W x H x D)**  
 175 x 220 x 138 mm

ARTICLE	ARTICLE NO	EAN-CODE	PU
CompactCube-Laser 3	036.150A	4 021563 696710	2