



Laserliner®

LuxTest-Master



Professional lighting intensity measuring instrument

Rev.0212



- **Measurement of lighting intensity** in workplaces, offices, public buildings and industry
- **Sensitive photodiode with cosine correction** for wide-angle light measurement
- **Relative measurement function** for reference and comparison measurement
- **Peak function** for registering fast changes in light levels
- Automatic and manual **range changeover**
- **Zeroing function** to adjust the sensor curve
- **Measurement variables:** Lux (lm/m²), foot candle (lm/ft²)
- **Min/Max display**
- **Hold function:** the current measured value is held in the display
- **1/4" tripod connection** for applications using tripods

TECHNICAL DATA

MEASURING RANGE	20,00 Lux; 200,0 Lux; 2,000 Lux; 20,000 Lux; 200,000 Lux
ACCURACY	± 3% (reference light bulb at 2854K)
COSINE ANGULAR DEVIATION	± 3% (30°) ± 6% (60°)
SENSOR	Silicon photodiode
SPECTRAL RANGE	320 nm...730 nm
DIMENSIONS (W x H x D)	89 x 190 x 42,5 mm
POWER SUPPLY	1 x 9V 6F22
WEIGHT	200 g



LC display with analogue bar graph



Removable protective cover



LuxTest-Master
inclusive carrying case
+ battery

Packaging dimension (W x H x D)
155 x 265 x 81 mm

ARTICLE	ARTICLE NO	EAN-CODE	PU
LuxTest-Master	082.130A	4 021563 680535	2

