



.aserliner

VideoScope Plus Set





Compact inspection camera for visual inspections of areas which are difficult to access featuring record function









- The camera head on the flexible cable transmits images directly to the LC monitor.
- **Problem locating:** the camera indicates what is behind or in objects, walls circuits or cables etc. even under worst light conditions, due to the LED-lighting.
- **REC-Function:** still picure and video can be recorded for a later analysis.
- Waterproof camera head and cable
- Ideal for difficult accessibly areas due to the small measuring head (ø 9 mm)
- Diversified application with 2 m camera.
- Powerful object lighting thanks to 4 high-performance LEDs
- Extraneous light reduction: contrasty LC-Display which provides an optimum display even under light irridation.
- External monitors operated via
 - TV Out connection
- **Formattable SDHC-Card**
- **Rotation:** The manual image rotation function enables the image to be rotated by 180° on the monitor.

TopGuide for 9 mm camera head

- **Guide sleeve** - optimal gliding on uneven surfaces

TECHNICAL DATA

VIDEOSCOPE PLUS

CAMERA HEAD

ø 9 mm, water-resistant, IP 68

CAMERA FOCUS F3 cm - F7 cm

SCREEN TYPE 3.5" TET colour display

CAMERA RESOLUTION 640 x 480 pixels

DISPLAY RESOLUTION 320 x 240 pixels

IMAGE / VIDEO RESOLUTION 720 x 480 pixel

IMAGE FORMAT / VIDEO FORMAT

LED 10 brightness levels

ZOOM

1.5x digital zoom in 10% increments MEMORY

Supports up to max. 8 GB SDHC card

PORT Mini USB

CONNECTIONS Micro-SD, analog-video

LENGTH OF FLEX CABLE 2 m

POWER SUPPLY

4 x AA 1.5 V batteries

OPERATING CONDITIONS 0°C...45°C, max. humidity 20...85% rH

no condensation, max. working altitude 4000 m above sea level

STORAGE CONDITIONS -10°C...60°C, max. humidity 80% rH

WEIGHT (incl. batteries) 0,58 kg

MATERIAL Aluminium

OUTSIDE DIAMETER 17 mm



ARTICLE	ARTICLE NO.	EAN CODE	PU
VideoScope Plus Set	082.256A	4 021563 691296	2



























VideoScope Plus Set

inclusive carrying case

- + TopGuide
- + USB/REC cable
- + batteries

Packing dimension (W \times H \times D) 340 x 275 x 123 mm