



The TMX 1000 forced-action pan mixer

is the right choice,
when it comes to mixing
prebagged material
at the construction site



› Materials and applications



TMX 1000 forced-action mixer


- Sturdy mixer for prebagged material with usable volumes of up to 80 litres (up to 4 sacks)
- For all types of plastic mortar, plaster, screed and concrete (-16 mm), the mixing tool can also be removed without requiring any other tool
- Bottom segment slidegate for emptying contents into a bucket or wheelbarrow
- Adapter for vacuum cleaner, for dust-free work
- Safety shut-down and lid detection
- Hard rubber wheels, therefore extremely stable
- Lashing eyes
- Compact size, fits through 80-cm-wide doors
- Easy to clean, extendible outlet shaft
- Robust design and motor protected from dirt
- Easy to clean, extendible outlet shaft
- **TMX 1000 TZ** model specially designed for terrazzo



· Removable discharge chute ·



· Dust extraction ·



· Mixing tool ·

Material (weight without the addition of water)

| | |
|--|---|
| Concrete up to 16 mm grain size | + |
| Cement screed | + |
| Synthetic resin screed (2K, 0.6/1.2 mm) | + |
| Cement and universal mortar | + |
| Lightweight masonry mortar | + |
| Cement plaster | + |
| Gypsum plaster | - |
| Heat insulation plaster | + |
| Natural stone mortar/cobblestone mortar | + |
| 2K pavement grout (up to 1.2 mm) | + |
| thin/fluid screed types | - |
| thin/fluid mortar types | - |
| Tile adhesive | - |
| Grout | - |
| Levelling compounds/self-levelling fillers | - |
| Packing mortar | + |
| Steel fibre mortar | + |
| Lightweight aggregate | + |
| Terrazzo (TMX 1000 TZ) | + |

TMX 1000 technical data

| | |
|---|----------------------|
| Capacity: | 100 litres |
| Usable volumes: | 80 litres |
| Motor output: | 2.0 kW |
| Voltage: | 230 V / 50 Hz |
| Speed of mixing tool: | 30 rpm ⁻¹ |
| Height to bottom edge of discharge chute: | 625 mm |
| Dimensions: | 840 x 755 x 1,170 mm |
| Noise emissions: | 86 dB |
| Weight: | 131 kg |
| Item no.: | 37080 |

TMX 1000 TZ technical data (with special mixing tool for terrazzo)

| | |
|---|----------------------|
| Capacity: | 100 litres |
| Usable volumes: | 80 litres |
| Motor output: | 2.0 kW |
| Voltage: | 230 V / 50 Hz |
| Speed of mixing tool: | 30 rpm ⁻¹ |
| Height to bottom edge of discharge chute: | 625 mm |
| Dimensions: | 840 x 755 x 1,170 mm |
| Noise emissions: | 86 dB |
| Weight: | 131 kg |
| Item no.: | 37084 |

Your Collomix specialised dealers:



Collomix GmbH | Daimlerstr. 9 | 85080 Gaimersheim | Germany
Tel. (08458) 32 98 0 | Fax (08458) 32 98 30 | info@collomix.de | www.collomix.com

