

## PLANO 3D GREEN

### Model

PLANO 3D green

### Technical details:

Item description	Line and point laser
Dimensions	150 x 95 x 125 mm
Leveling	Self-leveling
Measuring tolerance	±0.30 mm/m
Self-leveling range	±3°
Application range without handheld receiver (radius)	30 m*
Application range with handheld receiver (radius)	80 m*
Operating temperature	-10°C to +50 °C
Tripod adapter	1/4" + 5/8"
Protection class	IP54
Power supply	2 x 3.6-V Li-ion battery (3450 mAh)
Operating time (at 20°C, 68°F)	8 hrs (all diodes)
Laser class	2, DIN EN 60825-1 : 2014
Output power	< 1.0 mW
Wavelength	505-520 nm

### Included accessory:

- Rechargeable battery cell 18650
- PLANO 3D GREEN case
- LADEGERÄT AKKUZELLE
- NETZSTECKER LADEGERÄT
- PLANO 3D GREEN battery adapter



### CHARACTERISTICS:

- Two vertical 360° and one horizontal 360° laser lines enable universal use
- Highly visible laser lines, individually switchable
- Switchable inclination function
- Switchable pulse function for the use of the optional receiver REC LGD0 in difficult visibility conditions
- Compact, lightweight, handy

### APPLICATIONS:

- Horizontal leveling
- Inclination manual
- Vertical leveling
- 90° alignment
- Plumbing
- Aligning