


EVO 360

Model

EVO 360



CHARACTERISTICS:

- For use in horizontal or vertical operation
- Particularly easy and safe operation even for less experienced users
- Robust: IP66 protection and a drop resistance rating from one meter onto concrete
- Very high accuracy
- Plumbing point for marking out right angles
- Automatic height monitoring, stops the laser in the event of strong vibrations

APPLICATIONS:

- Horizontal leveling
- Vertical leveling

Technical details:

Item description	Horizontal/vertical rotation laser
Dimensions	179 x 143 x 211 mm
Leveling	automatic
Measuring tolerance	±0.10 mm/m
Self-leveling range	±5°
Application range without handheld receiver (radius)	20 m*
Application range with handheld receiver (radius)	300 m*
Operating temperature	-10°C to +50 °C
Rotation speed	600 rpm
Tripod adapter	5/8"
Protection class	IP66
Power supply	2 x 3.6-V Li-ion battery (3450 mAh)
Operating time (at 20°C, 68°F)	40 hrs
Laser class	2M, DIN EN 60825-1:2014+A1:2017
Output power	< 1.0 mW
Wavelength	635-650 nm

Included accessory:

- REC RRD1
- Rechargeable battery cell 18650
- LADEGERÄT AKKUZELLE
- NETZSTECKER LADEGERÄT
- C EVO 360

