

Standard Equipment

- ✓ 2 versions: Three-phase 400V/50Hz electric motor - Honda GXV340 petrol engine 8.1 kW
- ✓ Electric safety limit switch
- ✓ Thermal-magnetic switch with IP 55 no-volt coil and IP 67 plug (version with electric motor)
- ✓ Grid with bag-splitting blades: provides good visibility and protects against accidental contact
- ✓ Pneumatic wheels for excellent on-site mobility

220V/60Hz TPH

MOTOR AVAILABLE

✓ **MIX 750**



Mixing system

New geometry of the mixing paddles for fast and homogeneous batching and an optimum discharging speed. The drum base is generously-sized to reduce wear, the mixing paddles are fitted with rubber inserts for cleaning the mixing drum. The "mushroom" guard above the rotation shaft distributes the material evenly in the whole area of the drum. The newly-designed mixing gearmotor ensures torque even in the most demanding batches.



		MIX 360	MIX 750
Drum capacity	l	360	750
Mixing performance	l	200	480
Drum diameter	mm	952	1300
Paddle speed - electric motor/petrol engine	rpm	36/36	35/36
Motor power: electric motor/petrol engine	kW	3/8.1	4/8.1
Electric motor running current	A	7.2	9
SPL in operator's position: electric motor/petrol engine	dB(A)	70/88	70/88
Discharge height: max. - min.	mm	745-445	720-570
Machine weight: electric motor/petrol engine	kg	357/360	720/720
Dimensions w/l/h	mm	1080/1680/1155	1730/2279/1680