

## Standard Equipment

- ✓ Work positioning lever
- ✓ IP67 plug
- ✓ Trolley available for use with a gantry
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton IP65 pendant control
- ✓ Self-braking motor with magnetic device
- ✓ Bracket can be extended up to 1120 mm
- ✓ Hoist protection cover

## Optional Accessories

- ✓ Scaffold attachment

## Applications

It is ideal for lifting loads up to great heights because it has a high lifting speed (30 m/min). Maximum capacity remains unchanged for the entire arm extension so bulky materials can be lifted without the risk of striking against the structures.

**Ideal for construction sites up to 40 m high.**



150 kg



30 m/min



40 m



### ET 150 NEO

Maximum capacity	kg	150
Av. full load lifting speed	m/min	30
Max. working height	m	40
Ø steel rope	mm	4
Rope length	m	41
Electric power supply	V / Hz	230 / 50 Sph
Motor power rate	kW	0.8
Motor speed	rpm	1380
Running current	A	7.1
Machine weight	kg	48
SPL in operator's position	db(A)	<72
Dimensions w/l closed (open)/h	mm	330/770(1170)/520
Packing dimensions w/l/h	mm	390/810/590