

Standard Equipment

- ✓ Work positioning lever
- ✓ IP67 plug
- ✓ Trolley available for use with a gantry
- ✓ Upper limit safety device
- ✓ Multipin connector for changing the pendant control
- ✓ Self-braking motor with magnetic device
- ✓ Bracket can be extended up to 1120 mm
- ✓ Hoist protection cover

Optional Accessories

- ✓ Scaffold attachment
- ✓ Low voltage control 24V 50 m

Applications

The low noise level allows working without causing noise harmful to the operator's health and bothersome to others. TR VK 200 NEO has a high lifting speed (30 m/min) that allows to rapidly work on construction sites with great heights. **Ideal for construction sites up to 50 m high.**

Telescopic frame 720 mm - 1120 mm




200 kg



30 m/min



50 m



TR VK 200 NEO

Maximum capacity	kg	200
Av. full load lifting speed	m/min	30
Max. working height	m	50
Ø steel rope	mm	4
Rope length	m	51
Electric power supply	V / Hz	230 / 50 Sph
Motor power rate	kW	1.1
Motor speed	rpm	1320
Running current	A	10.1
Machine weight	kg	48
SPL in operator's position	db(A)	<75
Dimensions w/l closed (open)/h	mm	390/770(1170)/520
Packing dimensions w/l/h	mm	390/810/590