

BE 200 ET 200 N

High capacity hoists – 200 kg

BE 200 Standard Equipment

- ✓ Work positioning lever
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton pendant control, with emergency button and 16A IP67 EC flying plug
- ✓ Adjustable upper tie-rod
- ✓ Self-braking motor with magnetic device

Optional Accessories

- ✓ Rigid frame
- ✓ Trolley with brake for the gantry

Applications

Compact and lightweight, BE 200 can be transported and installed easily. Extremely versatile to install thanks to the variety of attachments available. The standard configuration envisages a bracket with an adjustable upper tie-rod.



Standard version

with adjustable upper tie-rod

		BE 200
Maximum capacity	kg	200
Av. full load lifting speed	m/min	20
Max. working height	m	30
Ø steel rope	mm	5
Rope length	m	31
Motor power rate 230V/50Hz	kW	0.75
Motor speed	rpm	1380
Running current	(A)	7.5
Machine weight	kg	30
SPL in operator's position	dB(A)	<74
Packing dimensions w/l/h	mm	250/820/350

ET 200 N Standard Equipment

- ✓ Work positioning lever
- ✓ IP67 plug
- ✓ Trolley available for use with a gantry
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton IP65 1.5 m pendant control
- ✓ Self-braking motor with magnetic device

Applications

Ideal for operations that do not require bracket extension.



		ET 200 N
Maximum capacity	kg	200
Av. full load lifting speed	m/min	19
Max. working height	m	30
Ø wire rope	mm	5
Rope length	m	31
Motor power rate 230V/50Hz	kW	0.75
Motor speed	rpm	1380
Running current	A	7.2
Machine weight	kg	42
SPL in operator's position	dB(A)	<70
Dimensions w/l/h	mm	330/770/520
Packing dimensions w/l/h	mm	350/820/500