

Masina de taiat asfalt / beton



MTA 400



MTA400-L



MTA400-H

Motorizare in 4 timpi, benzina, racire cu aer
Utilaj deosebit de robust si sigur in exploatare
Sistem de reglare a adancimii de taiere
Maneta de acceleratie si shock heavy-duty
Manere reglabile pentru o pozitie ergonomica

Masina de taiat este echipata cu rezervor de combustibil realizat din PPHD detasabil

| Masina de taiat Asfalt/Beton | MTA 400-H | MTA 400-H | MTA 400-L |
|------------------------------|-------------------|-------------|--------------|
| Tip motor | Honda GX200 | Honda GX270 | Loncin G270F |
| Combustibil | Benzina | Benzina | Benzina |
| Putere motor | 5,8 cp | 8,4 cp | 9 cp |
| Capacitate rezervor benzina | 3.1 l | 3.1 l | 6 l |
| Pornire motor | Manual | | |
| Inaintare utilaj | Manual | | |
| Rezervor apa | 25 l | | |
| Diametru max. disc | 400 mm | | |
| Adancime max. de taiere | 150 mm | | |
| Diametru prindere disc | 25.4 mm | | |
| Nivel de zgomot | 111 dB | | |
| Greutate utilaj | 90 kg | | |
| Dimensiuni L x l x h (mm) | 670 x 560 x 1.400 | | |



Contor ore ce afiseaza durata de utilizare si turatia motorului

Optional masina se poate echipa cu disc de taiere standard sau Long Life

Distribuitor local