

# Placa compactoare unidirectionala



Prodotto e certificato CE  
de Italia Star

## PC65-H

Powered by

**HONDA**  
POWER EQUIPMENT

Motorizare, consumabile si  
piese de schimb originale

Motorizare in 4 timpi, racire cu aer,  
alimentare cu benzina  
Maneta de acceleratie si shock heavy-duty  
Maner pliabil cu manson de protectie la vibratie  
Colturi rotunjite ale talpii

Utilizare:  
Compactare balastru,  
pavele de beton,  
asfalt, pamant, agregate



Placa compactoare	PC65-H
Tip motor	Honda GX160
Combustibil	Benzina
Putere motor	5.5 cp
Capacitate rezervor	3.1 l
Frecventa vibratii	5600 vpm
Dimensiune talpa (mm)	500 x 350
Forta de compactare	10.5 kN
Adancime max. de compactare	200 mm
Eficienta compactare	450 m2/h
Viteza de inaintare	40 cm/s
Nivel de zgomot	101 dB
Greutate utilaj	60 kg
Dimensiuni L/l/h (mm)	1030/420/950

Dotare de serie:  
kit roti pentru transport  
Covor cauciuc pentru pavele



Datorita manerelor pliabile si rotilor  
din dotare, se poate transporta usor si  
ocupa un spatiu redus

Distribuitor local