

MOVER 270e



✓ Higher slope (up to 65°) for the charging bucket. A descent control device can also be operated when the machine is cold



✓ Hatch with built-in safety valve

✓ Three-phase motor 5.5 kW

✓ Wider wear-proof shields inside the mixing tank

✓ Automatic pumping cycle, direct mixer drive for high performance and low maintenance



Mover 270 eb

Air screw compressor
MDVN series

Mod. 45 AP
(air output 4500 lit/min)



Recommended for Mover 270

Technical specifications	MDVN 45 AP
Air output (ISO 1217)	4500 lit/min - 159 CFM
Operating pressure	7 bar
Diesel engine	Perkins P404 C-22
No. of cylinders of the engine	4
Engine power kW (cv) at 3000 RPM	38 (51.7)
Max. engine RPM	2500
Min. engine RPM	1700
Length without tow bar	1920 mm
Length with tow bar	3380 mm
Width	1340 mm
Height	1300 mm
Weight without brakes	860 kg
Weight with brakes (*brakes not supplied as standard)	900 kg

↑ **Cod. 1107093** compressor
Cod. 1107164 20 m air hose
Cod. 1107165 10 m air hose
(air/water 20bar 25x37)

	Mover 190e	Mover 190eb	Mover 270e	Mover 270eb
Supply	-	230V/50Hz	230V/50Hz	400V/50Hz
Mixer motor power rate	kW	2,2	2,2	5,5
Power pack motor power rate	kW	-	0,75	-
Max. transportable grain size	mm	10/15	10/15	10/15
Average cycle output	l	150	150	200
Tank capacity	l	190	190	270
Loading height	mm	950	350	950
Dimensions width/length./h with bucket lifted	mm	1150/2970/1450	1150/2970/2285	1150/3150/1450
Weight	kg	590	700	630
Sound pressure level	dB(A)	< 57	< 57	< 57
Loading bucket	-	no	yes	no