

# Placa compactoare reversibila



Prodotto e certificato CE  
de Italia Star



## PCR160

Domenii de utilizare:

Compactare balast, agregate,  
pamant pentru constructii civile,  
industriale si infrastructura



Echipare standard: contor ce  
afiseaza nr. ore functionare si  
turatia motorului



Schimbarea acceleratiei si  
directiei de compactare  
tip heavy-duty  
se face mecanic

Placa compactoare reversibila	PCR160-S	PCR160-H	PCR160-L
Tip motor	Subaru EX21	Honda GX160	Loncin
Combustibil	Benzina	Benzina	Benzina
Putere motor	7 cp	5.5 cp	9.0 cp
Volum rezervor	3.6 l	3.1 l	3.6 l
Frecventa vibratii	4000 vpm	3600 rpm	4000 rpm
Dimensiune talpa	700x520 mm		
Dimensiune extensie	700x85 mm		
Forta de compactare	30.5 kN		
Adancime max. de compactare	500 mm		
Eficienta compactare	570 m <sup>2</sup> /h		
Sistem schimb directie	Mecanic		
Viteza intrare	25 cm/s		
Greutate utilaj	162 kg	160 kg	162 kg
Dimensiuni (mm) L/I/h	1000x460x1020		



Disponibila cu talpa din otel cu extensii  
sau din fonta

Distribuitor local