

HPSTAR 200-15

Racord rotativ +

Cadru rezistent cu
diametru de Ø 32 mm +



+ Roti pneumatice

Spalare cu presiune	HPSTAR 200-15
Presiune max.	200 bar
Debit	15 l/min. - 900 l/h
Turatie motor	3400 rpm
Tip pompa	Axial
Model pompa	Annovi Riverberi
Protectie temperatura	Termo valva
Motor	EX 27 DUL SH
Tip motor	OHC 4 timpi
Aspirare aer	Turbo
Putere max.	9.0 cp - 4000 rpm
Cilindri motor	265 cm ³
Combustibil	Benzina
Capacitate rezervor	6.1 l
Autonomie	3h
Pornire motor	la sfoara
Senzor lipsa ulei	Da
Greutate	56 kg
Dimensiuni L/l/h (mm)	700 x 700 x 1060

Echipare standard

Lance 1.1 m cu presiune ajustabila
Duza din ceramica ce asigura o viata ultra-indelungata
Furtun de presiune, 10 m lungime
Manometru presiune
Valva eliberare presiune
Kit aplicare detergent inclus
Protectie termica motor
Sasiu sudat mecanic cu tubulatura Ø30 mm
Protectie metal vopsita cu vopsea epoxy
Maner cadru detasabil pentru a o transporta mai usor
Roti pneumatice rezistente



www.italiastar.ro



Italia Star Com Due S.R.L.
Autostrada București - Pitești km. 13.2
Loc. Chiajna - Ilfov
Tel: 021.433.03.27
Fax: 021.433.03.26
info@italiastar.ro www.italiastar.ro