

Апарат заваръчен MIG/MAG и MMA с телоподаващо устройство REM Power WME_m MIG 200D



TECHNICAL DATA

MODEL	WME _m MIG 401	WME _m MIG 501
<i>Frequency (Hz)</i>	50/60	50/60
<i>Setting range (A)</i>	15-400	15-500
Output max at 60% duty cycle, (MIG)	400 A/34,0 V	500 A/39,0 V
Output max at 100% duty cycle, (MIG)	271 A/27,6 V	387 A/33,4 V
<i>Output max at 60% duty cycle, (MMA)</i>	350 A/34,0 V	490 A/39,6 V
<i>Output max at 100% duty cycle, (MMA)</i>	271 A/30,8 V	380 A/35,2 V
<i>Output max at 60% duty cycle, (TIG)</i>	350 A/24,0 V	490 A/29,6 V
<i>Output max at 100% duty cycle, (TIG)</i>	271 A/20,8 V	380 A/25,2 V
<i>Open circuit voltage (V)</i>	65 V	65 V
<i>Electrode diameter (mm)</i>	1,6-4,0	1,6-4,0

STANDARD ACCESORIES

MODEL	WME _m MIG 401	WME _m MIG 501
MIG TORCH	3 m	3 m
CLAMP	Ø7	Ø7
GAS HOSE	Ø5.5 x 8 (0.75m)	Ø5.5 x 8 (0.75m)
RETURN CABLE	3 m	3 m