PS2 500 50mm/2in Submersible Pump 110V/60Hz

Item Number: 0009113

PS2 500

Application

>> Lightweight, portable, single phase submersible pumps are designed to handle water and solids. Built for the demands of construction, mining, municipality and farm applications. Which pump must be selected — Calculation examples Pumps performance curves — overview <<



Additional Advantages

- These high performance single-phase submersible pumps are capable of handling solids up to .4 inches, ideal for job sites needing fast dependable dewatering.
- Lightweight, compact design with heavy-duty, strain relief power cord offers a highly durable pump that is still easy to transport and install.
- Built-in thermal protection prevents motor damage due to impeller blockage, reducing service repairs.
- Silicon carbide-faced double mechanical seals run in an isolated oil-filled cavity, allowing for seal lubrications, cooling and overall motor protection.
- Silicon carbide faced double mechanical seals run in an isolated oil-filled cavity, allowing for seal lubrication, cooling and overall motor protection.
- Oil lifter provides lubrication to seal faces during operation mimimizing the risk of seal failure due to overheating.
- Preliminary v-ring (lip seal) shields the mechanical seal from abrasive wear due to suspended debris in pumping fluid. .



| Description | Metric | Imperial |
|--|----------------------|-------------------|
| Discharge diameter | 50 mm | 2 in |
| Length x width x height | 185 x 185 x 305 mm | 7.3 x 7.3 x 12 in |
| Operating weight | 9,5 kg | 21 lb |
| Shipping weight (including packaging) | 12,7 kg | 28 lb |
| Shipping size (LxWxH) | 350 x 250 x 230 mm | 13.8 x 9.8 x 9 in |
| Max. head | 12 m | 39.5 ft |
| Max. discharge | 236 I/min | 62.4 US gpm |
| Max. pressure | 1,17 bar | 17 psi |
| Solid size capacity | 6 mm | 0.2 in |
| Motor type | Single phase/60 H | łz |
| Voltage | 110 V | 110 V |
| Current (full load/start @ 110V) | 6,1/12,5 A | 6.1/12.5 A |
| Speed | 3.270 1/min | 3,270 rpm |
| Max. power output according to DIN-ISO 3046* | 0,48 kW | 2/3 hp |
| Cable length | 10 m | 32 ft |
| Cable size | 1,31 mm ² | 16 AWG |
| Impeller material | Urethane rubber | .17 |
| Impeller type | Semi-vortex | |

Standard Package - PS2 500

Above package include electrical supply cable, operator's manual and parts book.

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Wednesday, August 29, 2012



