40V Max Brushless 165mm Circular Saw

15012G

HEAVY DUTY BRUSHLESS

SEWEHN

Takte

Product Statement

40V Max Brushless 165mm Circular Saw

The 40V Max XGT Brushless 165mm (6-1/2") Circular Saw (HS012G) provides best in class cutting speed, with the ability to cut up to 40% faster then the 18V equivalent (DHS680). The Makita-built brushless motor delivers 5,200 RPM for high-speed cutting performance, with a large cutting capacity of 57mm at 90-degrees.

Constant Speed Control maintains cutting speed under load for optimum cutting performance while the saw is also equipped with Makita's Extreme Protection Technology (XPT) improving the tool's operation in harsh conditions. For added convenience the saw also features Auto-Start Wireless System (AWS) for wireless power-on and power-off communication between the equipped tool and compatible dust extractor.



Product Overview



Positive Bevel Stop

Electric Brake

Product Specifications

HEAVY DUTY BRUSHLESS



Max. cutting capacities at 0°	57mm		
Max. cutting capacities at 45°	41mm		
Max. cutting capacities at max bevel	51mm		
Bevel capacity	0°- 50°		
Blade diameter	165mm (6-1/2")		
Bore diameter	20mm		
No load speed	5,200rpm		
Overall length	352mm		
Skin Weight	2.48kg		
Weight (with battery)	3.48kg (BL4040)		
Voltage	40V Max		
Compatible batteries	BL4025* / BL4040* / BL4050F / BL4080F *Recommended		

- **High Power Output** the high power 40Vmax XGT Li-Ion battery allows for continuous operation in heavy-duty applications. With cutting speeds up to 40% faster than the 18V equivalent.
- Lightweight Design The base and blade case are made of magnesium reducing the overall weight of the tool while maintaining strength and rigidity.
- **Positive Bevel Stop** allows for fast and accurate bevel adjustment to common bevel angles. With a maximum bevel capacity of 0-50°, positive stops at 22.5° and 45°.
- **Auto-Start Wireless System (AWS)*** compatible with AWS the HS012G can be paired with a compatible vacuum for on demand dust extraction. AWS uses Bluetooth to wirelessly power on and off the extraction unit using the tools trigger.
- **Constant Speed Control –** Constant speed control maintains blade speed under load for optimum cutting performance.
- **Soft Start –** Blade starts slowly then rapidly accelerates to maximum speed to reduce the initial start up shock.
- **Electric Brake** Maximises productivity and user safety by rapidly slowing the wheel rotation after the switch has been released.

*AWS receiver sold separately

Advantages



Heavy Duty



Heavy duty power with rapid to 40% faster then the 18V equivalent

Safety protection with electric brake and soft start for user safety

Safety

Innovation



Constant Speed Control Maintains blade speed under load

Compatibility



AWS for power communication between enabled tool and optional dust extractor.

Max. cuttin

Max. cuttin Max. cuttin bevel

Bevel capac

Blade diam

Bore diame

No load spe

Overall leng

Skin weight

Weight (wit

Voltage

Our Range



HEAVY DUTY BRUSHLESS

	NEW - HS012G	HS003G	HS004G	HS009G	HS011G	RS001G	RS002G
ing capacities at 0°	57mm	66mm	60mm	85mm	101mm	65mm	95mm
ing capacities at 45°	41mm	45.5mm	43mm	61mm	71mm	45mm	70mm
ing capacities at max	57mm	34mm	41mm	44mm	51mm	38mm	54.5mm
acity	0°-50°	0°- 56°	0°- 48°	-1°- 60°	-1°- 60°	0°-53°	0°-56°
neter	165mm (6-1/2")	185mm (7-1/4")	185mm (7-1/4")	235mm (9-1/4")	270mm (10-5/8")	185mm (7-1/4")	260mm (10-1/4")
neter	20mm	20mm	20mm	25.4mm	25.4mm	20mm	30mm
beed	5,200rpm	6,000rpm	6,000rpm	4,000rpm	3,500rpm	6,400rpm	4,000rpm
ngth	352mm	331mm	337mm	413mm	453mm	446mm	489mm
nt	2.48kg	3.4kg	3.7kg	4.4kg	4.8kg	4.4kg	5.0kg
vith battery)	3.48kg (BL4040)	4.4kg (BL4040)	4.7kg (BL4040)	5.4kg (BL4040)	5.8kg (BL4040)	5.6kg (BL4050F)	6.3kg (BL4050F)
	40V Max	40V Max	40V Max	40V Max	40V Max	40V Max	40V Max

Accessories

Standard Accessories			Optional Accessories				
Thakita	B-62991	165mm x 20 x 25T Efficut TCT Saw Blade			Efficut Saw Blades	<u>Link to Accessories</u> <u>Website</u>	
			Ň		BlueMak Saw Blades	Link to Accessories Website	
	783203-8 Hex Wre	Hex Wrench 5mm			M Force Saw Blades	Link to Accessories Website	
	196961-1Dust Extraction Nozzle164095-8Guide Rule	HE		Multi-Purpose Saw Blades	Link to Accessories Website		
					Knot & Nail Saw Blades	Link to Accessories Website	
			THE REAL PROPERTY AND A DECIMAL PROPERTY AND	Aluminium Saw Blades	Link to Accessories Website		
					AWS Bluetooth Receiver	198901-5	

Accessories

Optional Accessories Guide Rail Adapter 196953-0 Suits HS012G & DHS680 Aluminium guide rail 199140-0 1.000mm 194368-5 1,400mm 199141-8 1,500mm 194925-9 1,900mm 194367-7 3,000mm **Protective guide rail** holder E-05664 (suits 2 x 1400 rails with storage for 2 clamps) Clamp set to suit guide 194385-5 rails 199826-6 G-Clamp **Quick Clamp**

196664-7

Bevel Guide set to suit

guide rails



Guide rail replacement strips Type 1 – 3m running strips Type 2 – 3m splinter guide Type 3 – 3m guide rail seat

> **Guide rail joiner** 1 joiner set 2 joiner sets

Extraction System

