

# 40V Max Brushless 30mm SDS Plus Rotary Hammer

Quick Change Chuck



HEAVY DUTY BRUSHLESS



HR009G



MARABY  
DAILY  
ПРОДАЖА

## 40V Max Brushless 30mm SDS Plus Rotary Hammer

The 40V Max. Brushless 30mm Rotary Hammer delivers high performance with 3.9 joules of hard-hitting impact energy. That impact energy allows you to drill holes in masonry up to a 30mm diameter quickly and efficiently.

Anti-Vibration Technology (AVT) actively reduces the tools vibration through a series of count weight mechanisms and vibration absorbing housing. These designs significantly reducing the vibration transferred to the user for more comfortable use of the tool over extended periods of time.

Compatible with AWS\* the HR009G can be paired with a compatible vacuum for on demand dust extraction. AWS uses Bluetooth to wirelessly power on and off the extraction unit using the tools trigger. In addition, the HR009G is compatible with a wide variety of dust management options including the onboard dust extraction system DX11.

\*AWS receiver sold separately



# Product Overview



Quick Change SDS Plus Chuck

Constant Speed Control

Active Feedback Sensing Technology (AFT)

Variable speed control but trigger & dial



Torque Limiter



МАГАЗИН  
БАЛТИЙСКИЙ  
ПРОФЕСИОНАЛ

# Product Specifications



HEAVY DUTY BRUSHLESS



Max. drilling capacities in masonry	TCT Bit: 30mm Core Bit: 80mm Diamond Core Bit: 80mm
Chuck Type	SDS Plus Quick Change Chuck
Impact energy	3.9j
No load speed	0-840rpm
Impact rate	0-4,500ipm
Sound Pressure	91dB(A)
Vibration	9.1m/s <sup>2</sup>
Overall length	439mm
Skin weight	5.5kg
Weight (with battery)	6.5kg (BL4040)
Voltage	40V Max

- **Quick Change SDS Plus Chuck** – the HR009G is equip with a quick change chuck. With the ability to quickly change the chuck between an SDS Plus change and conventional keyless chuck.
- **Anti-Vibration Technology (AVT)** – extremely low vibration is achieved by 4 active vibration absorbing mechanisms. A counterweight, vibration absorbing rear handle, anti-vibration side grip and rubber joint construction.
- **Torque Limiter** – Torque limiting clutch engineered to prevent gear damage by automatically disengaging gears during a bind-up situation.
- **Auto-Start Wireless System (AWS)\*** – Auto-Start Wireless System (AWS) which utilises Bluetooth technology for wireless power-on/off communication between tool and dust extractor. (\*AWS Transmitter sold separately)
- **Constant Speed Control** – Constant speed control automatically applies additional power under load for optimum performance.
- **Active Feedback Sensing Technology (AFT)** – sensors shut down the tool in the event of a kickback providing user protection. If the bit rotation is suddenly forced to stop such as the bit jamming the motor automatically shuts down.
- **Variable Speed Trigger & Dial** – Variable speed dial and trigger enables user to match the speed to the application.

## Heavy Duty Power



Powered by XGT 40V Max batteries  
Allowing for continuous heavy duty operation

## Dust Management



Compatible with multiple options for various environments

## Innovation



Anti-vibration technology provides extremely low vibration of  $9.1\text{m/s}^2$

## Safety



Active feedback sensors shut down the tool in the event of a kickback

# Our Range



HEAVY DUTY BRUSHLESS

	HR001G	HR002G	HR007G	HR008G	HR009G	HR005G	HR006G
Max. drilling capacities in masonry	TCT Bit: 28mm Core Bit: 54mm Diamond Core Bit: 65mm	TCT Bit: 28mm Core Bit: 54mm Diamond Core Bit: 65mm	TCT Bit: 28mm Core Bit: 54mm Diamond Core Bit: 65mm	TCT Bit: 30mm Core Bit: 80mm Diamond Core Bit: 80mm	TCT Bit: 30mm Core Bit: 80mm Diamond Core Bit: 80mm	TCT Bit: 40mm Core Bit: 105mm	TCT Bit: 52mm Core Bit: 160mm
Chuck Type	SDS Plus Standard	SDS Plus Quick Change Chuck	SDS Plus Standard	SDS Plus Standard	SDS Plus Quick Change Chuck	SDS Max	SDS Max
Impact energy	2.8j	2.9j	3.0j	3.9j	3.9j	8.0j	21.4j
No load speed	0-980rpm	0-980rpm	0-980rpm	0-840rpm	0-840rpm	250-500rpm	150-310rpm
Impact rate	0-5,000ipm	0-5,000ipm	0-5,000ipm	0-4,500ipm	0-4,500ipm	1,450-2,900ipm	1,100-2,250ipm
Sound Pressure	95dB(A)	93dB(A)	95dB(A)	91dB(A)	91dB(A)	91dB(A)	99dB(A)
Vibration	7.0m/s <sup>2</sup>	7.5m/s <sup>2</sup>	8.6m/s <sup>2</sup>	9.1m/s <sup>2</sup>	9.1m/s <sup>2</sup>	5.0m/s <sup>2</sup>	8.5m/s <sup>2</sup>
Overall length	358mm	389mm	473mm	422mm	439mm	520mm	610mm
Skin weight	3.2kg	3.3kg	3.2kg	5.4kg	5.5kg	6.9kg	11.7kg
Weight (with battery)	4.2kg (BL4040)	4.3kg (BL4040)	4.2kg (BL4040)	6.4kg (BL4040)	6.5kg (BL4040)	8.2kg (BL4050F)	14.3kg (BL4050F)
Voltage	40V Max	40V Max	40V Max	40V Max	40V Max	40V Max	80V Max (40V x2)

Standard Accessories		
	331886-4	Depth Gauge
	194683-7	Bit Grease
	443122-7	Cloth
	821875-2	Plastic Case



Optional SDS Plus Drilling Accessories		
	Nemisis II 4 Cutter	<a href="#">Link to Accessories Website</a>
	V-Plus 2 Cutter	<a href="#">Link to Accessories Website</a>
	Dust Extraction Bits	<a href="#">Link to Accessories Website</a>
	Demolition Bits	Range available Page 212. Acc Catalogue
	Dry Diamond Core Bit	Range available Page 192. Acc Catalogue
	Dust Extraction Cup Set	195179-1
	Dust Extraction Vacuum Adaptor	P-80488
	AWS Bluetooth Receiver	198901-5

## On-Board Dust Extraction Set DX11 (191G00-4)

265mm Max. Bit Length  
2 stage: 160mm & 265mm

