



**Cordless Polisher**  
**PV001G 180 mm (7")**




**40V** LI-ION  
**max**

## Cord-free Polishing



No load speed by dial  
**600 - 2,200** min<sup>-1</sup>

### Continuous run time

Tested with load: 3.5-4.0kg  
 Battery: BL4025 (on a full battery charge)

at 2,200min<sup>-1</sup>

about **9**min

at 600min<sup>-1</sup>

about **42**min





**BL**  
MOTOR

**Reduction of damage to Car body**

Elastomer bumpers are positioned at the portions most likely to hit car body.



Lock-on switch

Variable speed control by trigger


Dust cover

**XPT** eXtreme Protection Technology



**Constant speed control**

minimizes the reduction in pad speed to provide stable polishing.



**Variable speed control by dial**

Max rotation speed can be selected to suit application.



**Easy-to-grip head shape**

enables user to easily press the pad to the car body in applications such as scratch removal with polishing compound.



**3-Position loop handle**




**Accessories**

**For Wool pad hook & loop type**

**Wool pad 180**  
Part No. 192629-7

**Sleeve 18**  
Part No. 262542-4

Backing pad	
Spindle thread	Part No.
M14x2	743053-3
5/8-11	743052-5
M16	743054-1



**For wool bonnet**

**Wool bonnet 180**  
Part No. 794176-0

**Sanding lock nut**

Spindle thread	Part No.
M14-48	224515-5
5/8-48	224517-1
M16-48	224523-6

**Rubber pad**  
Part No. 743012-7



**Loop handle**  
Part No. 413F67-9



**Side handle**  
Part No. 158237-4



**Charging Time**

	Fast Charging	
	DC40RA	DC40RC
BL4020 2.0Ah	22 min	30 min
*BL4025 2.5Ah	28 min	38 min
*BL4040 4.0Ah	45 min	67 min
*BL4050F 5.0Ah	50 min	85 min
BL4080F 8.0Ah	76 min	170 min

\*1 Recommended battery

**Cordless Polisher**

**PV001G 180 mm (7")**

- Variable Speed
- Constant Speed
- Soft Start
- Hook & Loop
- Carrying Case

**Standard Equipment :**

Loop handle, Side grip (country-specific), Hex wrench, Wool pad (country-specific), Pad (country-specific), Wool bonnet (country-specific), Rubber pad (country-specific), Lock nut (country-specific), Lock nut wrench (country-specific), Dust cover (country-specific), Battery, Charger


Brush pad capacity	180 mm (7")
Pad diameter	165 mm (6-1/2")
No Load Speed (RPM)	By trigger: 0 - 2,200 By dial: 600 - 2,200
Vibration Level	2.5 m/s <sup>2</sup> or less
Sound Pressure Level	80dB(A)
Dimensions	w/ BL4020, BL4025: 516 × 196 × 195mm (20-1/4 × 7-3/4 × 7-5/8")
	w/ BL4040: 531 × 196 × 195mm (20-7/8 × 7-3/4 × 7-5/8")
	w/ BL4050F, BL4080F: 550 × 196 × 195mm (21-5/8 × 7-3/4 × 7-5/8")
Net weight	3.0 - 4.4 kg (6.6 - 9.7 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge.  
The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.  
Items of standard equipment and specifications may vary by country or area.

**Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202203



МАГАЗИН  
**БАШ МАЙСТОРА**<sup>®</sup>  
ПРОФЕСИОНАЛНИ РЕШЕНИЯ