

Makita

18V Brushless 400mm Chainsaw

LXT

DUC407X2



Product Statement

The DUC407 features a gear reduction system to maximise the performance of the 0.61kW of Max output power provided by the Brushless motor. This delivers a max chain speed of 7.7m/s which allows the narrow 1.1mm chain to smoothly cut through hardwoods.

Tool-less chain tension adjustment makes replacing, loosening or tightening bars & chains a quick and easy job. The electric brake stops the chain quickly once the trigger is released and the lock off button helps to reduce the risk of unexpected start up.




Product Overview



Ergonomic Handles for Comfortable Use

Mechanical Chain Brake

Lock-Off Trigger



Gear Reduction Mechanism

Tool-less Chain Adjustment



Product Specification Sheet



| | |
|----------------------------|--------------|
| Motor | Brushless |
| Bar retention | Tool-less |
| Oil tank capacity | 150mL |
| Chain speed | 7.7m/s |
| Guide bar length | 400mm |
| Standard chain | 3/8" / 0.043 |
| Overall length (Powerhead) | 428mm |
| Skin weight | 2.9kg |
| Weight (with battery) | 3.5kg |
| Voltage | 18V |

- **Gear Reduction System** – increases torque to allow the unit to power through tough hardwood.
- **Tool-less Bar and Chain Tensioning** – allows for easy on going maintenance and tensioning of the chain.
- **Lock Off Trigger** – reduces the risk of accidental start up.
- **Electric Brake** – slows the chain speed quickly once the trigger is released.
- **Chain Oil Window** – provides visible sight to check bar & chain oil has been added before start up.
- **Ergonomic Handles** – designed at the optimum angles for comfortable long term use.

Power



Gear reduction system provides increased torque to power through hardwoods

Functional



Tool-less bar & chain tension adjustment

Ergonomics










Ergonomic front and rear handles for comfortable vertical or horizontal use

Functional



Large opening allows for easy oil filling and viewing of level

Our Range

| | DUC407 - NEW | DUC254 | DUC302 | DUC353 | DUC355 | DUC400 | DUC405 |
|----------------------------|---|--|---|---|---|---|---|
| |  |  |  |  |  |  |  |
| Motor | Brushless | Brushless | Brushed | Brushless | Brushless | Brushless | Brushless |
| Bar retention | Tool-less | Captive nut | Tool-less | Tool-less | Captive nut | Tool-less | Captive nut |
| Oil tank capacity | 150mL | 140mL | 85mL | 200mL | 200mL | 200mL | 200mL |
| Chain speed | 7.7m/s | 0 - 24m/s | 8.3m/s | 0 - 20m/s | 0 - 20m/s | 0 - 20m/s | 0 - 20m/s |
| Guide bar length | 400mm | 250mm | 300mm | 350mm | 350mm | 400mm | 400mm |
| Standard chain | 3/8" / 0.043 | 3/8" / 0.043 | 3/8" / 0.043 | 3/8" / 0.043 | 3/8" / 0.043 | 3/8" / 0.043 | 3/8" / 0.043 |
| Overall length (Powerhead) | 428mm | 256mm | 316mm | 443mm | 443mm | 443mm | 443mm |
| Skin weight | 2.9kg | 2.7kg | 3.5kg | 4.0kg | 4.3kg | 4.2kg | 4.5kg |
| Weight (with battery) | 3.5kg | 3.3kg | 4.7kg | 5.2kg | 5.5kg | 5.4kg | 5.7kg |
| Voltage | 18V | 18V | 36V (18V x 2) | 36V (18V x 2) | 36V (18V x 2) | 36V (18V x 2) | 36V (18V x 2) |

| Standard Accessories | | |
|---|---------------------------|----------|
|  | Guide Bar 40cm | 191G17-7 |
|  | Guide Bar Cover | 419560-5 |
|  | Saw Chain 3/8" / 0.043 | 191H03-4 |

| Optional Accessories | | |
|---|-----------------------------|---------|
|  | 1/4" Hex Diamond File | D-73754 |
|  | Round File 2 pc | D-67371 |
|  | File with Guide & Handle | D-70954 |
|  | Roll Up Kit | D-72160 |



МАГАЗИН МАЙСТОР
БАШ ПРОФЕСИОНАЛНИ РЕШЕНИЯ