SIMPLEX soft-face mallets • TPE-mid / superplastic; with aluminium housing and high-quality wooden handle

EH 3137.





Product Description

The SIMPLEX series 3137 is available with the insert combination of TPE-mid / superplastic. The grey, medium hard TPE-mid insert (series 3203) is a thermoplastic elastomer that does not leave behind any colour marring or - unlike a conventional rubber mallet - any undesired black marring. Its hardness is comparable to that of the rubber composition insert (series 3202). The superplastic insert (series 3207) allows for a more powerful impact force than the rubber insert. It is a medium hard plastic insert made of extruded and extremely homogeneous material. Compared to injection moulded plastic inserts, it is therefore considerably more wear-resistant and durable.

The extra light aluminium housing with built-in handle protection sleeve allows the user to easily apply and control the right amount of impact force. It also makes the soft-face mallet a tool with minimum weight that is easy to carry along.

Damping vibrations and shaped ergonomically, the high-quality wooden handle has a double coat of varnish in the grip area and is thus resistant to dirt.

In line with the smart SIMPLEX principle, all components are replaceable and can be retrofitted. This translates to savings in both money and resources.

This version is available in sizes ranging from D30mm to D60mm.

- Product features:
- SIMPLEX soft-face mallet with the insert combination of TPE-mid (grey, medium hard, no marring) / superplastic (white, medium hard, very durable).
- The extra light aluminium housing with built-in handle protection sleeve allows the user to easily apply and control the right amount of impact force.
- High-quality, vibration-damping, and ergonomically shaped wooden handle; grip area with double coat of varnish (resistant to dirt).
- All parts can be replaced / retrofitted, resulting in great savings in cost and resources.
- Available in sizes of D30mm to D60mm.

Application Areas

Place fragile tiles, positioning and adjusting of light/delicate workpieces , joiner's work, prototyping, door construction, furniture assembly

Material

Handle

Wood

insert 1

- TPE-mid, grey
- Non-marringMedium hard

Wiedia

- insert 2
- Superplastic, white
- Medium hardVery durable
- Wear-resistant
- Wedi Teolote
- Housing
- Aluminium Al

Order information

Ø		Din —	nensions Length x Width x Height	Ĭ	GTIN	proficl@ss 5.0	ecl@ss 10.1	Art. No.
[mm]			[g]					
30	90	295	295 x 90 x 30	170	4030618304746	AAA905c002	21-04-09-16	3137.030
40	115	325	325 x 115 x 40	365	4030618304753	AAA905c002	21-04-09-16	3137.040
50	135	370	370 x 135 x 50	575	4030618304760	AAA905c002	21-04-09-16	3137.050
60	150	405	405 x 150 x 60	820	4030618304777	AAA905c002	21-04-09-16	3137.060

Application example



RoHS compliant Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 14.06.2023.

Does not contain Proposition 65 substances No Proposition 65 substances included.

https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.

