## **KÄRCHER**

### **HDS 6/14-4 CX**

The HDS 6/14-4 CX is a single-phase hot water high-pressure cleaner in the Compact class with 4-pole, water-cooled electric motor and in-built hose reel with 15-metre pressure hose.





Made in Germany









Order no.

1.170-902.0


- Economical ecolefficiency mode
- Four-pole water-cooled electric motor

Technical data		
EAN code		4054278167886
Supply voltage	Ph/V/Hz	1 / 230 / 50
Flow rate	I/h	240 - 560
Working pressure	bar / MPa	30 - 140 / 3 - 14
Temperature (for supply 12 °C)	°C	min. 80 - max. 155
Connected load	kW	3.6
Consumption of heating oil or gas at full load	kg/h	3.5
Consumption of heating oil in ecolefficiency mode	kg/h	2.8
Power cable	m	5
Fuel tank	I	15
Weight (with accessories)	kg	114.4
Weight incl. packaging	kg	123.2
Dimensions (L × W × H)	mm	1215 × 650 × 920

Users i	must	receive	training	on	this	device
---------	------	---------	----------	----	------	--------

Equipment		
Spray gun		EASY!Force Advanced
High-pressure hose	m	15 / DN 6, 250 bar
Spray lance	mm	1050
Power nozzle		
Soft Damping System (SDS)		
Integrated high-pressure hose reel		
Pressure switch-off		
Integrated fuel and cleaning agent		
tank		_
Included in the scope of supply.		

Included in the scope of supply









- ecolefficiency mode efficient and environmentally friendly, even when used for prolonged periods.
- Reduces fuel consumption and CO2 emissions by 20%.
- Precise detergent dosing unit with rinse function.

#### Ease of use

- Intuitive operation thanks to the large single-button selector switch.
- Large tank opening with filling chute.
- Convenient system care bottle can be changed from the outside.



#### Storage

- Lockable accessory compartment for nozzles, tools, etc.
- Integrated hose reel with 15 m pressure hose.
   For a large operating radius and effortless stowage (CX versions).
- Integrated lance holder for transport.






























		Order no.	Description	
TRIGGER GUNS				
Spray guns				
EASY!Force Advanced	1	4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	
EASY!Force conversion kit 1 - from high-pressure hose	2	4.111-050.0	For retrofitting Karcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle.	
EASY!Force conversion kit 2 - from machine	3	4.111-051.0	Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.	
EASY!Force conversion kit 3 - high-pressure gun	4	4.111-052.0	Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner.	
Servo control			7 // // // //	
Servo Control, < 750 l/h	5	4.118-007.0	Servo control for water flow and pressure control (< 750 l/h) on trigger gun.	
SPRAY LANCES				
Rotating spray lances				
Spray lance, 1050 mm, rotatable	6	4.112-000.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	-
LED nozzle light	7	2.680-002.0	Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.	
Spray lance, 250 mm, rotatable	8	4.112-027.0	Spray lance, 250 mm, rotatable, ergonomic	
Spray lance, 400 mm, rotatable	9	4.112-024.0	Spray lance, 400 mm, rotatable, ergonomic	
Spray lance, 600 mm, rotatable	10	4.112-007.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 840 mm, rotatable	11	4.112-006.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 1550 mm, rotatable	12	4.112-018.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 2050 mm, rotatable	13	4.112-021.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance extender, 1000 mm	14	4.112-048.0	Spray lance extension with EASY!Lock connection. Length 1000 mm.	

lacksquare Included in the scope of supply.  $\ \square$  Available accessories.

# HDS 6/14-4 CX, 1.170-902.0, 2024-01-15

#### **KARCHER**





















		Order no.	Paradistina	
SPRAY LANCES		Order no.	Description	_
Double lance				_
Double lance, 960 mm	15	121120160	960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable	lг
·	15	2.112-016.0	for agricultural use (e.g. stable cleaning).	╧
Angular spray lance		Ì	.94	
Spray lance for toilets and rain gutters	16	4.112-029.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance				Ц
Flexible lance, 1050 mm	17	4.112-035.0	1050 mm flexible lance with variable bend from $20^\circ$ to $140^\circ$ , ideal for cleaning difficult to reach areas, e.g. gutters.	
High pressure articulated joint	18	4.112-057.0	For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.	
Gutter cleaner				
Gutter cleaning lance	19	2.112-015.0	The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the specia nozzle the gutter can be cleaned without removing the cover plates.	1 -
Undercarriage spray lance				
Underbody lance	20	4.112-032.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle	7			
Additional handle for EASY!Lock spray lances	21	4.321-380.0	Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task. Regularly changing your posture relieves the strain on your body, making work more relaxed. Thanks to the 360°-rotatable spray lance, the additional handle can simply be fully rotated whilst working for greater flexibility.	:
KÄRCHER POWER NOZZLE				
Power nozzle spray angle 25°			CX	
Power nozzle 25°, 036	22	2.113-005.0	Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.	.
HP nozzle spray angle 0°		7		T
Power nozzle 0°, 040	23	2.113-001.0	High-pressure nozzle with powerful jet for extremely stubborn dirt.	
Power nozzle spray angle 15°				$^{+}$
Power nozzle 15°, 036	24	2.113-043.0	Flat jet nozzle for stubborn dirt.	Ic
Power nozzle spray angle 40°				$\pm$
Power nozzle 40°, 040	25	2.113-003.0	Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	lΓ
HIGH-PRESSURE HOSES			, , , , , , , , , , , , , , , , , , ,	j
Standard				
High-pressure hose, 15 m, DN 6, 250 bar, 1 × EASY!Lock / 1 × AVS-hose reel connection	26	6.110-036.0	With AVS hose reel connection and high-pressure hose (ID 6, 15 m long, up to 250 bar pressure) with EASY!Lock hand screw connection.	
	27	6.110-037.0	High-pressure hose, (ID 6), 15 m long, for up to 250 bar working pressure. With ANTI!Twist for hose reels with AVS connection The other end has an EASY!Lock hand screw connection.	e [
Standard with unions on both sides				$^{+}$
High-pressure hose, 10 m, DN 10, 220 bar, 2 × EASY!Lock	28	6.110-041.0	Impressive values and basic equipment: 10 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	

















		1		-
		Order no.	Description	
HIGH-PRESSURE HOSES				
Standard with unions on both sides				
High-pressure hose, 10 m, DN 8, 315 bar, 2 × EASY!Lock	29	6.110-031.0	High-pressure hose (DN 8) suitable up to 315 bar pressure. With innovative EASY!Lock manual screw fitting on both sides, ANTI!Twist and 10 m long.	
High-pressure hose, 15 m, _ 8, 315 bar	30	6.110-033.0	15 m long high-pressure hose, DN 8, with ANTI!Twist and equipped with time-saving EASY!Lock manual screw fitting on both sides.	
High-pressure hose, 15 m, DN 8, 315 bar, 2 × EASY!Lock	31	6.110-030.0	15 m long high-pressure hose, DN 8, with ANTI!Twist and time-saving EASY!Lock manual screw fitting on both sides.	
High-pressure hose, 20 m, DN 8, 315 bar, 2 × EASY!Lock	32	6.110-032.0	20 m long high-pressure hose (DN 8) equipped with the time-saving and robust EASY!Lock manual screw fitting on both sides. Approved for pressures up to 315 bar.	
High-pressure hose, 30 m, DN 8, 315 bar, 2 × EASY!Lock	33	6.110-014.0	Comfortable length (30 m) and innovative EASY!Lock manual screw fitting: High-pressure hose (DN 8) with ANT!!Twist for pressures up to 315 bar.	_
High-pressure hose, 15 m, DN 10, 220 bar, 2 × EASY!Lock	34	6.110-042.0	Equipped with innovative EASY!Lock manual screw fitting and suitable for pressures up to 220 bar 15 m long high-pressure hose (DN 10).	:
High-pressure hose, 20 m, DN 10, 220 bar, 2 × EASY!Lock	35	6.110-043.0	20 m in length and the extremely time-saving and comfortable EASY!Lock manual screw fitting on both sides are some of the main features of this high-pressure hose (DN 10).	
High-pressure hose, 25 m, DN 10, 220 bar, 2 × EASY!Lock	36	6.110-044.0	Impressive values and basic equipment: 25 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	_
High-pressure hose, 40 m, DN 10, 220 bar, 2 × EASY!Lock	37	6.110-045.0	40 m long high-pressure hose with EASY!Lock system for the time-saving manual screw connection (both sides). Nominal size (DN) 10, working pressure up to 220 bar.	1
High-pressure hose, 15 m, DN 12, 210 bar, 2 × EASY!Lock	38	6.110-059.0	Designed for working pressures up to 250 bar: High-pressure hose (DN 12) with a length of 15 m. Has the comfortable EASY!Lock manual screw fitting on both sides.	
High-pressure hose, 40 m, DN 12, 210 bar, 2 × EASY!Lock	39	6.110-060.0	With EASY!Lock manual screw fitting and lots of room for manoeuvre thanks to 40 m in length: High-pressure hose (DN 12) with EASY!Lock manual screw fitting on both sides. Suitable for working pressures up to 250 bar.	
Longlife 400		7 //		Ī
High-pressure hose Longlife, 20 m, DN 8, 400 bar, 1 × EASY!Lock / 1 × AVS-hose reel connection	40	6.110-028.0	20 m high-pressure hose (ID 8), for up to 400 bar pressure. With AVS hose reel connection and double steel reinforcement. EASY!Lock hand screw connection at other end of the hose.	
Longlife 400 with unions on both sides				١
High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, 2 × EASY!Lock	41	6.110-024.0	1.5 m short high-pressure hose (DN 8). Comfortable EASY!Lock manual screw fitting on both sides for robust and quick connections. Durable and designed for up to 400 bar pressure.	
High-pressure hose Longlife, 30 m, DN 8, 400 bar, 2 × EASY!Lock	42	6.110-023.0	Robust high-pressure hose with double steel core, ANTI!Twist and EASY!Lock manual screw fitting on both sides. Nominal size DN 8, 30 m long, for up to 400 bar pressure.	

<sup>☐</sup> Available accessories.

























		Order no.	Description	
HIGH-PRESSURE HOSES				
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 20 m, DN 8, 400 bar, 2 $\times$ EASY!Lock	43	6.110-027.0	High-pressure hose with ANTI!Twist, EASY!Lock manual screw fittings and double steel core. 20 m long, nominal size DN 8, EASY!Lock manual screw fitting on both sides.	
High-pressure hose Longlife, 15 m, DN 8, 400 bar, 2 × EASY!Lock	44	6.110-029.0	The double steel core ensures a particularly long life of this 15 m long high-pressure hose (DN 8), which is approved for pressures up to 400 bar.	
Food industry version with unions on both side	es			_
High-pressure hose food grade, 15 m, DN 6, 250 bar, 2 × EASY!Lock	45	6.110-063.0	15 m long high-pressure hose (ID 6), food grade, with AVS hose reel connection, EASY!Lock hand screw connection and grey, non-marking outer covering.	
High-pressure hose food grade, 10 m, DN 8, 250 bar, 2 × EASY!Lock	46	6.110-051.0	High-pressure hose (ID 6), 10 m long, with grey, non-marking outer covering. Approved for use in the food industry. With quick and robust EASY!Lock hand screw connection at both ends.	
High-pressure hose food grade, 20 m, DN 8, 250 bar, 2 × EASY!Lock	47	6.110-052.0	Suitable for use in food industry: 20 m long high-pressure hose (ID 8) with grey, non-marking outer covering, ANTI!Twist and EASY!Lock hand screw connections.	Г
Longlife food design				
High-pressure hose food grade, 20 m, DN 8, 400 bar, 1 × EASY!Lock / 1 × AVS-hose reel connection	48	6.110-075.0	M. Th.	
Longlife food design with screw connections at	t both	ends	7/01	_
High-pressure hose food grade Longlife, 10 m, DN 8, 400 bar, 2 × EASY!Lock	49	6.110-053.0	With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, ANTI!Twist and EASY!Lock hand screw connection at both ends.	
High-pressure hose food grade Longlife, 20 m, DN 8, 400 bar, 2 × EASY!Lock	50	6.110-054.0	Durable high-pressure hose with double steel reinforcement and blue, non-marking and animal fat resistant outer covering. 20 m long with EASY!Lock hand screw connections.	
Special hoses			7 (, )	
High-pressure hose curved, 1.5 m, DN 8, 400 bar, 1 $\times$ EASY!Lock / 1 $\times$ M22 $\times$ 1.5	51	6.110-068.0	For connection to hose reels: high-pressure hose, with M $22 \times 1.5$ connection and curved EASY!Lock hand screw connection. $1.5$ m long, suitable for up to 400 bar working pressure.	: [
WEED CONTROL				T
WR 50	52	2.114-013.0	In combination with a hot water high-pressure cleaner from Kärcher, the 50 cm wide weed remover WR 50 is ideal for removing weeds. It comes with an adaptive chassis and nozzle adapter.	
WR 20	53	2.114-014.0	For thorough weed removal: The WR 20 weed remover for use with a hot water high-pressure cleaner from Kärcher. Equipped with a 20 cm wide nozzle bar and nozzle adapter.	
WR 100	54	2.114-015.0	Comfortable and fast weed removal: WR 100 weed remover with chassis, 100 cm wide nozzle bar and integrated nozzle adapter for use with hot water high-pressure cleaners.	
WR 10	55	2.114-016.0	In combination with hot water high-pressure cleaners our WR 10 weed remover enables fast and thorough weed removal. With 10 cm spray head and nozzle adapter.	
QUICK CONNECT				Т
Quick coupling	56	2.115-000.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread.	

<sup>☐</sup> Available accessories.























00		7-05		
		Order no.	Description	
QUICK CONNECT				
Male coupling	57	2.115-001.0	Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 $\times$ 1.5 external thread.	
DRUM AND TANK CLEANING				
Add-on kit mud sucker	58	2.641-798.0	For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps.	
OTHER HP ACCESSORIES				
Jet gun	59	2.869-067.0	Short set-up time, easy transport, instant switch off – the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.	1 [
FLUE PIPE				
Flue gas adapter	60	4.656-149.0	Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for	
	61	4.656-080.0	connection to a stack system).	
ROTARY NOZZLES (DIRT BLASTERS)				
Dirt blaster, large				
Dirt blaster, large, 040	62	4.114-041.0	The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzl and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	e [
MULTIPLE-JET NOZZLES				
Angled vario nozzle 0-90°				
Angled Vario nozzle, 050	63	4.113-007.0	Variable angle nozzle for spray angle adjustment from $0^{\circ}$ to $90^{\circ}$ . For easy adjustment to all kinds o soiling and surfaces.	of [
STEAM JET NOZZLE / NOZZLE PROTECTOR / RO	OLLOV	ER NOZZLE	7.0	
Steam jet nozzles				
Steam jet nozzle 50°	64	4.116-000.0	Steam jet nozzle with 50°fan jet. For cleaning and thawing in steam stage. For thawing sand and gravel, de-icing formwork material or de-waxing vehicles.	
Steam jet nozzle 40°, 040	65	2.114-000.0	Brass steam nozzle for operation of the HDS in steam stage.	Г
NOZZLE UNION / SPACER				
Nozzle union		0		
Nozzle screws	66	4.112-011.0	Nozzle screws with protectors for high-pressure and power nozzles	
PIPE CLEANING				Ť
Pipe cleaning hose, ID 6				
Pipe cleaning hose, ID 6, 10 m, max. 250 bar	67	6.110-046.0	The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, ID 6, 20 m, max. 250 bar	68	6.110-008.0	The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, ID 6, 30 m, max. 250 bar	69	6.110-047.0	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning nozzle				
Pipe cleaning dirt blaster D21/040	70	4.765-001.0	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.	
			·	

<sup>☐</sup> Available accessories.



























				T
PIPE CLEANING		Order no.	Description	_
Pipe cleaning nozzle				
Pipe cleaning dirt blaster D30/040	71	4.765-004.0	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.	[
Pipe cleaning nozzle 120	72	5.763-089.0	Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.	
Pipe cleaning nozzle	73	5.763-015.0	16 mm pipe cleaning nozzle with internal thread. Various jet directions for	[
	74	5.763-016.0	environmentally-friendly cleaning of blocked drains and pipes.	
	75	5.763-017.0	Pipe cleaning nozzle with inner thread. Different spray directions. The hose moves freely through the pipe. (R $1/8$ " connection, $3 \times 30$ ° backwards, diameter 30 mm.)	
Rotating pipe cleaning nozzle	76	6.415-428.0	Pipe cleaning nozzle with four rotating jets and inner thread. Different spray directions. The hose moves freely through the pipe. With R 1/8" connection.	
FLOOR AND HARD SURFACE CLEANER				
Hard Surface Cleaner FRV 30				
Hose fastening attachment kit	77	2.642-528.0	Suction cup for fixing the suction hose to smooth surfaces.	
Dirt trap attachment kit	78	2.642-532.0	Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	[
FR 30 Me surface cleaner			V / 6 ( )	
Hard Surface Cleaner FR 30 Me	79	2.111-013.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Machine-specific nozzle kits for FR				
Nozzle kit for FR, 500 l/h - 650 l/h	80	2.640-401.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).	[
Machine-specific nozzle kits for FRV			/ (, 9	
Nozzle kit for FRV, 040	81	2.642-431.0	Machine-specific nozzle kit Kärcher power nozzles and jet nozzle for FRV 30.	
FRV 30 Me surface cleaner		7 //		
FRV 30 Me Surface Cleaner	82	2.111-012.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	[
Extension hose FRV 30 Me and FRV 50 Me	83	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	[
FOAM SYSTEMS				
Cup foam lance				
Cup foam lance Advanced 1, 400 l/h - 600 l/h	84	4.112-063.0	High-quality and robust cup foam lance Advanced 1 with spray angle adjustment and main body made of Ecobrass. Suitable for Kärcher high-pressure cleaners with a flow rate of 400 to 600 l/h.	

<sup>☐</sup> Available accessories.

# **ACCESSORIES FOR HDS 6/14-4 CX 1.170-902.0**



























		T		
		Order no.	Description	
FOAM SYSTEMS				
Cup foam lance				
Cup foam lance DUO Advanced 1, 400 l/h - 600 l/h	85	4.112-067.0	DUO Advanced 1 cup foam lance with two-litre detergent tank and direct switching to high-pressure cleaning. Suitable for Kärcher pressure washers with a flow rate of 400 to 600 l/h.	
Cup foam lance Basic 1, 350 l/h - 600 l/h	86	4.112-053.0	For high-pressure cleaners with a flow rate of 350-600 l/h: new, robust and very high-quality Basic 1 cup foam lance with outstanding foam quality while consuming half as much cleaning ager	nt.
1-litre cleaning agent container for cup foam lance basic	87	5.071-414.0	For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0).	
1-litre cleaning agent container for cup foam lance advanced	88	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	
Inno Foam Kit				
Inno Foam Set	89	2.112-008.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	
Easy Foam Set				
Easy Foam Set	90	2.112-011.0	HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	
Nozzle kits for Inno/Easy Foam Set		. 1	7 ()	
Nozzle kit 060 for Inno / Easy Set 600-700 l/h	91	2.111-018.0	Optimal adaptation to different machine outputs for economic use.	
Foam nozzle mounting kit				
Foam nozzle attachment kit	92	2.112-013.0	Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	
MIXERS AND INJECTORS				
Machine-specific nozzle kit with order no. 4.63	37-033	3.0	<u>C</u>	
Nozzle kit 500-700 l/h	93	4.769-009.0	For HDS 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union	
Nozzle insert with order no. 4.637-032.0				
Nozzle insert up to 1,100 l/h - high pressure	94	4.769-003.0	Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Nozzle insert up to 1,100 l/h - low pressure	95	4.769-001.0	For low pressure with machines up to 1.100 l/h	
COUPLING PARTS				
Rotary coupling				
Rotary coupling	96	4.111-021.0	Reliably prevents twisting of HP hoses. Connection Easy!Lock. Handle protection	
Connector		•		
Screw socket for surface cleaners and Servo Control controllers	97	4.111-022.0	For attaching high-pressure nozzles and accessory parts to the HD trigger gun (with nozzle screws) – $1 \times M$ 22 $\times$ 1.5/1 $\times$ M 18 $\times$ 1.5.	
Y distributor	98	4.111-024.0	Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	





























		Order no.	Description	
COUPLING PARTS				
Connector				
Short spray unit	99	4.111-038.0	For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). No compatible with triple nozzles.	ot 🗆
EASY!Lock adapter			.94	
Adapter 1 M22AG-TR22AG	100	4.111-029.0	Adapter 1 to connect the old hose with the new hose	
Adapter 2 M22IG-TR22AG	101	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	
Adapter 3 M22IG-TR22AG	102	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	
Adapter 4 TR22IG-D11	103	4.111-032.0	Adapter 4 to connect the new gun with the old swivel hose	
Adapter 5 TR22IG-M22AG	104	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	
Adapter 6 TR22IG-M22AG	105	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	
Adapter 7 M18IG-TR20AG	106	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	107	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	
Adapter hose extension 9 TR	108	4.111-037.0	Adapter 9 to connect the new hose with the new hose	
Adapter 12 rotary coupling EASY!Lock 22 IG - M22 × 1.8 AG	109	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	
HOSE REELS				
Automatic, self-winding hose reels for wall mo	untin	3		
Automatic plastic hose reel incl. high-pressure hose, 15 $\ensuremath{\text{m}}$	110	2.639-257.0	Spring-mounted and ready-to-use automatic hose reel for wall mounting. Simplifies handling of the high-pressure hose, shortens set-up times and increases occupational safety.	ş 🗆
Automatic hose reel, powder-coated steel / plastic, 20 m	111	6.392-074.0	Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Automatic stainless steel / synthetic material hose drum, 20 m	112	6.392-083.0	Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	

<sup>☐</sup> Available accessories.



# **ACCESSORIES FOR HDS 6/14-4 CX 1.170-902.0**



























	l .			
		Order no.	Description	
HOSE REELS				
Automatic, self-winding hose reels for wall mo				
Automatic hose reel, coated, 20 m	113	6.392-106.0	Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	
Hose reel, automatic, basalt grey-coated, 20 m	114	6.392-105.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. For example: order no. 6.110-011.0 (ID 8, 20 m, 315 bar) or order no. 6.110-028.0 (ID 8, 20 m, 400 bar Longlife).	
Automatic hose reel, stainless steel, includes swivel holder, 20 m	115	6.392-076.0	Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
Automatic stainless steel hose reel, 40 m	116	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	
Powder-coated swivel holder	117	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	
Stainless steel swivel holder	118	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	
Automatic, self-winding hose reel attachment l	kit			
Attachment kit automatic hose reel HDS C	119	2.110-012.0	Complete automatic hose reel attachment kit for HDS compact class. Simple installation and all unit functions are accessible. Offers maximum convenience when winding and unwinding the HP hose. Contains: Automatic hose reel, HP hose and all connection parts.	
Attachment kit automatic hose reel holder HDS	120	2.110-013.0	Holder includes connection material for installing an automatic hose reel to machines from the HDS compact class.	; 🗆
FACADE AND SOLAR PANEL CLEANING				
Brushes			/ 1.9	
Drive for roller brush 500	121	4.762-584.0	Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.	
Splash guard for roller brush 500	122	4.762-621.0	Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.	
Roller brush 500 soft	123	4.762-623.0	Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.	
Roller brush 500 medium	124	4.762-624.0	Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.	
Roller brush 500 hard	125	4.762-625.0	Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.	
Brush hard	126	6.960-133.0	Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.	

# **ACCESSORIES FOR HDS 6/14-4 CX 1.170-902.0**























		T		
		Order no.	Description	
FACADE AND SOLAR PANEL CLEANING				
Brushes				
Brush medium	127 6.960-134.0 Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.			
Brush soft	128	6.960-135.0	.0 For simple installation on telescopic lances or high-pressure lances from K\u00e4rcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.	
Telescopic lances				
TL low pressure adapter	129	4.580-097.0	TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.	
Telescopic lance TL 7 F	130	4.762-609.0	elescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With ractical quick-release fasteners for simple retraction and extension.	
Telescopic lance TL 7 H	131	4.762-610.0	Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix Telescopic thanks to quick-release fastenings. Up to 7 m reach.	i. 🗆
Telescopic lance TL 10 H	132	4.762-611.0	Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	
Telescopic lance TL 10 C	133	4.762-612.0	arbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fastent oultifunctional use for cleaning facades, windows or solar panels.	
Telescopic lance TL 14 C	134	4.762-613.0	Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.	
TL high pressure adapter	135	4.775-154.0	TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	
WET BLASTING ATTACHMENT				
Wet blasting attachment (without nozzle)			/ (, <del>·</del>	
Wet blasting attachment with flow control (without nozzles)	136	4.115-000.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	137	4.115-006.0	Addition of spray agent to the high pressure jet. For paint stripping, rust removal and descaling. Assembly on spray lance instead of high-pressure nozzle. Without water flow regulation	
Nozzle kits for wet jet unit				
Nozzle kit for wet jet unit 040	138	2.112-019.0	Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.115-000.0   4.115-006.0.	
Boron carbide nozzle				
Boron carbide nozzle, for machines up to 1,000 l/h	139	6.415-084.0	In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	
DRUM AND TANK CLEANING		<u>'</u>		
Barrel and tank cleaning				
Barrel cleaner BC 14/12	140	2.112-020.0	The BC 14/12 barrel cleaner is a spray unit for the interior cleaning of containers and barrels – especially oak barrels with a capacity of between 225 and 600 litres.	
		1		

# **ACCESSORIES FOR HDS 6/14-4 CX 1.170-902.0**























ADD ON KITS  Flame monitoring attachment kit  Flame monitoring attachment kit for HDS  Compact Class  WATER CONNECTION		Order no. 2.642-711.0	Description		
Flame monitoring attachment kit Flame monitoring attachment kit for HDS Compact Class	41	2.642-711.0			
Flame monitoring attachment kit for HDS Compact Class	41	2.642-711.0			
Compact Class	41	2.642-711.0			
WATER CONNECTION			A light sensor monitors the burner flame. The fuel supply is shut off if the flame goes out.		
Geka coupling					
Geka connector with hose barb, R 1/2" 14	42	6.388-461.0	with hose liner		
Geka connector with hose barb, R 3/4" 14	43	6.388-455.0			
Geka connector with hose barb, R 1" 14	44	6.388-465.0	with hose barb		
Geka connector with internal thread, R 1" 14	45	6.388-458.0	with female thread		
Suction filter					
Water suction filter 14	46	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 $\mu$ m mesh, R 3/4" and R 1" connection, without non-return valve		
Suction filter with check valve 14	47	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.		
Water fine filter					
Universal water fine filter, 25 µm	48	2.637-020.0	Water fine filter, mesh size 25 µm, max. temperature 50 °C. Protects the machine from small dirt particles in the water. Water volume up to 1200 l/h. 3/4" connection, with 1" adapter.		
Water fine filter, with adapter	49	4.730-102.0	Fine-mesh water filter, $125 \mu m$ , max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4°, with adapter, 1°.		
Water fine filter, 100 µm, R 1"	50	2.638-270.0	Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".		
Water supply hose		/ /			
Water supply hose 15	51	4.440-038.0	NW 13 R1" / R 3/4", up to 30 °C		
15	52	4.440-207.0	NW 19 R1" / R 3/4", up to 85 °C, for pick-up	Г	
WASHING BRUSHES		0		t	
Push-on washing brush					
Push-on wash brush	53	4.113-001.0	For universal use for surface cleaning. Mounted using clamp directly at the spray lance. TR thread connection		
Rotating washing brush				_	
Rotating wash brush for < 1000 l/h machines, hylon bristles	54	4.113-004.0	The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 60°C. (M 18 × 1.5, replaceable brush insert).		

# **ACCESSORIES FOR HDS 6/14-4 CX 1.170-902.0**





		Order no.	Description				1	
WASHING BRUSHES								
Rotating washing brush					7			
Rotating wash brush for < 800 l/h machines, natural bristles	155		Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to $60^{\circ}$ C, M $18 \times 1.5$ (replaceable brush insert).					
		•						